


120 V Powerled linear

Long runs and flexibility are the primary features of our smooth PowerLED linears. A sleek, driverless connection ensures smooth and continuous light in every application.



*Not available for model 6009LED

Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
6009LED	9"	3 W	250 lm	300 lm	80	3000 K	120 V
6012CC	12"	4 W	330 lm	400 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
6024CC	24"	8 W	675 lm	800 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
6036CC	36"	12 W	1080 lm	1200 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
6048CC	48"	16 W	1300 lm	1800 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V

Specifications

Switch-selectable CCT (models 6012, 6024, 6036, 6048)

Over 50,000 hours of service life

Dimmable with regular low-voltage electronic dimmers

Smooth linear wide spread

Minimal heat emission

Robust construction

Multiple fixtures can be linked together (up to 200W)

Refer to website for dimmer compatibility

5-year warranty

Accessories

6000-ACCE06
6" extension cord

6000-ACCE24
24" extension cord

6000-ACCE60
60" extension cord

6000-ACCLR
Kit of left and right L connectors

6000-ACCPC
6' power cord

6000-JB
Junction box

Finish

● **SBA** Sandblasted aluminum

Order example


6012CC-SBA
12" LED cove strip with a 4W LED array with 330 lumens at 3000K in a sandblasted aluminum finish

Note


Junction box model 6000-JB or power cord model 6000-ACCPC are required for installation. Sold separately.

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

6009LED




6012CC



6024CC



6036CC



6048CC

