
Round flush mount

Our LED flush mounts incorporate Edge-Lit technology, eliminating hot spots or glare. With 3 sizes to choose from, every application is covered.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
CFLEDR06	6"	11 W	700 lm	750 lm	90	3000 K	120 V
CFLEDR06-4K	6"	11 W	700 lm	750 lm	90	4000 K	120 V
CFLEDR10	10"	17 W	880 lm	1000 lm	90	3000 K	120 V
CFLEDR10-4K	10"	17 W	880 lm	1000 lm	90	4000 K	120 V
CFLEDR14	14"	26 W	1600 lm	2100 lm	90	3000 K	120 V
CFLEDR14-4K	14"	26 W	1600 lm	2100 lm	90	4000 K	120 V

Specifications

Integrated dimmable driver
 Over 50,000 hours of service life
 Superior LED performance and lifespan
 Smooth 360° wide spread
 Minimal heat emission
 Frosted lens
 Edge-lit technology
 Cast aluminum construction
 Suitable for wet locations
 Refer to website for dimmer compatibility
 Ideal operating temperature:
 -20° to 40° C
 5-year warranty

Finish

- **BK** Black (3000 K only)
- **SN** Satin Nickel
- **WH** White

Order example


CFLEDR06-SN
 CFLEDR06 6" round ceiling flush mount
 in a satin nickel finish

Note


Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.



CFLEDR06



CFLEDR10



CFLEDR14

