

---

## Square flush mount

Our LED flush mounts incorporate Edge-Lit technology, eliminating hot spots or glare. With 3 sizes to choose from, every application is covered.



**JA8**  
CERTIFIED



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>CFLEDSQ06</b>	6"	11 W	700 lm	750 lm	90	3000 K	120 V
<b>CFLEDSQ06-4K</b>	6"	11 W	700 lm	750 lm	90	4000 K	120 V
<b>CFLEDSQ10</b>	10"	17 W	880 lm	1000 lm	90	3000 K	120 V
<b>CFLEDSQ10-4K</b>	10"	17 W	880 lm	1000 lm	90	4000 K	120 V
<b>CFLEDSQ14</b>	14"	26 W	1600 lm	2100 lm	90	3000 K	120 V
<b>CFLEDSQ14-4K</b>	14"	26 W	1600 lm	2100 lm	90	4000 K	120 V

### Specifications

Integrated dimmable driver  
 Over 50,000 hours of service life  
 Superior LED performance and lifespan  
 Smooth 360° wide spread  
 Minimal heat emission  
 Frosted lens  
 Edge-lit technology  
 Cast aluminum construction  
 Suitable for wet locations  
 Refer to website for dimmer compatibility  
 Ideal operating temperature:  
 -20° to 40° C  
 5-year warranty

### Finish

- **BK** Black (3000 K only)
- **SN** Satin Nickel
- **WH** White

### Order example

#### CFLEDSQ06-WH


CFLEDSQ06 6" square ceiling flush mount in a white finish

#### Note


Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.



#### CFLEDSQ06



#### CFLEDSQ10



#### CFLEDSQ14

