

Copernico 500 suspension polished white

SPECIFICATIONS

1608038A



Design By

Carlotta de Bevilacqua

Collection

Design



Specifications

| | |
|------------------------------------|---------------------------------|
| Delivered lumens | 1963lm |
| Light output ratio | 85.35lm/W |
| Power consumption | 23W |
| Led type | 21W Array* |
| CCT (Correlated Color Temperature) | 3000K |
| CRI (Color Rendering Index) | >80 |
| Life expectancy | 50000Hrs |
| Control type | Dimmable 2-Wire |
| Input Voltage | 120-277V |
| Driver | ADVANCE - 1 x XI050C100V054XPL1 |

Colors & Finishes

Pol. White RAL9003

Materials

- Made in anodized aluminum

Features & Accessories

- 7 concentric mobile rings obtained from an aluminum plate support a circuit of 384 LEDs
- The rings rotate independently on two different axes enabling light to be directed
- Numerous spatial configurations can be obtained by adjusting the rings as needed
- When the device is closed up it is completely flat
- Also compatible with 0-10V dimming

Dimensions



standard length
min. 19 11/16" - max. 78 3/4"
min. 50 cm - max. 200 cm

extended length
min. 19 3/4" - max. 216 "
min. 50 cm - max. 548 cm


Packaging

1 Box

1 x 21-15/16" x 21-9/16" x 5" / 10.36 lbs - 55.5 cm x 54.5 cm x 12.5 cm / 4.7 kg

Light distribution

Direct/Indirect



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Luminaire weight

6.17 lbs / 2.8 kg

Warranty

5 year limited warranty