Design By

Ross Lovegrove

Collection

Design

Specifications

Delivered lumens	1346lm
Light output ratio	46lm/W
Power consumption	29W
Led type	24W C.O.B.*
CCT (Correlated Color Temperature)	2700K
CRI (Color Rendering Index)	>93
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire**
Input Voltage	120-277V
Driver	HATCH - 1 x XTC32-0700P-UNV-I

**Reverse or forward phase (120v only)

Colors & Finishes

Polished Aluminum (Pebbles)

Stainless Steel (Reflector)

Materials

- Lighting unit in die-cast aluminum
- Reflective units made of injection-molded thermoplastic material with metallic finish
- Reflector in stainless steel

### Features & Accessories

- Extended cable length

Dimensions

13 3/4"
35 cm

22 3/8"
56.9 cm

Standard length
Min. 37 15/16" - Max. 102 15/16"
Min. 96.4 cm - Max. 261.4 cm

Extended length
Min. 37 15/16" - Max. 215 3/4"
Min. 96.4 cm - Max. 548 cm

ø 27 9/16"
ø 70 cm

Packaging

1 Box

1 x 31-9/16" x 31-9/16" x 9-15/16" / 31.42 lbs - 80 cm x 80 cm x 25 cm / 14.25 kg

Light distribution

Indirect

Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Luminaire weight

23.7 lbs / 10.75 kg

Warranty

5 year limited warranty

We reserve the right to change specifications of our products.
For the latest product information please visit www.artemide.net

Artemide®