## SUMMIT

# **SBC682CFTWIN**



33.63" x 23.75" x 24.25" (H x W x D)

24" wide indoor/outdoor dual tap cold brew coffee dispenser for built-in or freestanding commercial or residential use, with stainless steel exterior and caster set

#### **Highlights:**

Commercially approved to NSF-7 standards

Meets residential guidelines for home wet bars and similar spaces

Complete dual tap coffee dispensing kit includes Nitrogen tank, regulator, and all the hardware needed to pour the perfect brew

#### **Product Features:**

Full-sized cold brew coffee dispenser	5.6 cu.ft. interior can accept a full half barrel or quarter keg, or up to three sixth barrels or Cornelius style kegs	
Commercially approved	ETL-S listed to NSF-7 standards and meets UL-471 for use in commercial settings	
Weatherproof design	Solid 304 grade stainless steel construction allows placement in the outdoors	
Built-in capable	Front-breathing design allows fully recessed installation under counters	
Complete dual tap kit	Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs	
Dual tap system	Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs	
Automatic defrost	Reduced user maintenance with auto defrost operation	
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit	
Tap cool system	Interior tube allows you to extend the cold air flow up into draft tower, ensuring coffee freshly tapped stays chilled	






### **SBC682CFTWIN Specifications:**

Overview	
Height of Cabinet	33.63" (85 cm)
Width	23.75" (60 cm)
Depth	24.25" (62 cm)
Depth with Handle	26.25" (67 cm)
Depth with door at 90°	46.75" (119 cm)
Capacity	5.6 cu.ft. (159 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	305.0kWh/year
Amps	1.25
Voltage/Frequency	115 V AC/60 Hz
Weight	120.0 lbs. (54 kg)
Shipping Weight	130.0 lbs. (59 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101083995
Kegerator	
Door Swing	RHD
Reversible	Yes
Tap Kit	Yes
Height with Tap	51.5" (131 cm)
Number of Taps	2
Adjustable Shelves	Yes
Shelf Type	Chrome
Shelf Qty	2
Thermostat Type	Digital
Fan Type	Interior and Exterior
Refrigerant	R600a
Refrigerant Amount	1.06 oz.
High Side PSI	150.0
Low Side PSI	50.0

Inter Height	26.75" (68 cm)
Interior Width	20.0" (51 cm)
Interior Depth	19.0" (48 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	34°F to 68°F (1°C to 20°C)
Sound Level	34.0 db







ELEC. CORD