



**24" C-SERIES
Refrigerator**



eco friendly
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Glass Door Model (Indoor)



Solid Door Model (Outdoor)

MODELS	DESCRIPTION
HC24RB-4-1R/L	Indoor C-Series Refrigerator Solid Stainless Steel Door
HC24RB-4-2R/L	Indoor C-Series Refrigerator Solid Panel Ready Door
HC24RB-4-3R/L	Indoor C-Series Refrigerator Stainless Steel Glass Door
HC24RB-4-4R/L	Indoor C-Series Refrigerator Panel Ready Glass Door
HC24RO-4-1R/L	Outdoor C-Series Refrigerator Solid Stainless Steel Door
HC24RO-4-2R/L	Outdoor C-Series Refrigerator Solid Panel Ready Door

KEY PRODUCT FEATURES AND BENEFITS

- 800 BTU/hr capacity delivers commercial grade cooling performance
- Variable speed compressor minimizes sound; up to 30% quieter than competitors
- Full extension shelving provides faster and safer product access with no reaching in the back of the cabinet; shelves fully extend on vibration dampened stainless steel ball bearing glides
- Commercial-grade all stainless steel interior provides superior durability and easy cleaning

Quick Features:

- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready door to match your design style
- Outdoor models include a full stainless steel exterior; indoor models feature a black vinyl exterior for built in applications
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Storage for up to 144 cans



24" C-SERIES
Refrigerator

MODEL NUMBERS		HC24RB	HC24RO
MODEL DESCRIPTION		24" Indoor Refrigerator	24" Outdoor Refrigerator
ATTRIBUTES			
Perlick Anti-Condensation System		NO	NO
Energy Star Certified		YES	YES
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm.)	23-7/8" (606 mm.)
	Depth - in. (mm)	24" (610 mm.)	24" (610 mm.)
	Height - in. (mm)	34-1/4" (870 mm.)	34-1/4" (870 mm.)
STANDARD OPENING DIMENSIONS	Width - in. (mm)	24" (610 mm.)	24" (610 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)	24-7/8" (632 mm.)
	Height - in. (mm)	34-1/2" (876 mm.)	34-1/2" (876 mm.)
INTERNAL VOLUME Net. Cu. Ft.		5.2 cu. ft.	5.2 cu. ft.
SHIPPING WEIGHT Lbs. (kg.)		183 lbs (83.01 kg.)	183 lbs (83.01 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph
	Running Load Amps	1.9 amps	1.9 amps
	Electrical Connection	Cord connected	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P
	Cord Length	6'	6'
	Defrost Initiation	Automatic	Automatic
	Defrost Type	Off cycle	Off cycle
	Thermostat	Digital	Digital
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (62g)	R600a (62g)
	Expansion Device	Capillary Tube	Capillary Tube
	Temperature Settings F°(C°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)
	Heat Rejection (at 75°F)	450 BTU/hr	450 BTU/hr
	Pull Down Capacity	800 BTU/hr	800 BTU/hr
	Front Vented	Yes	Yes
PLUMBING		None Required	None Required

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

ACCESSORIES

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
66736	Caster Kit for HP24/HC24/HA24 models
RS-24-24D	Divider Shelf for HP24/HC24/HA24 models

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com.




24" C-SERIES
Refrigerator

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HC24RB-4-1L	HC24RB4C-00-SLS0R	Left	No
HC24RB-4-1R	HC24RB4C-00-SRS0R	Right	No
HC24RB-4-2L	HC24RB4C-00-PL00R	Left	No
HC24RB-4-2R	HC24RB4C-00-PR00R	Right	No
HC24RB-4-3L	HC24RB4C-00-TLS0R	Left	No
HC24RB-4-3R	HC24RB4C-00-TRS0R	Right	No
HC24RB-4-4L	HC24RB4C-00-RL00R	Left	No
HC24RB-4-4R	HC24RB4C-00-RR00R	Right	No
HC24RB-4-1LL	HC24RB4C-00-SLSLR	Left	Yes
HC24RB-4-1RL	HC24RB4C-00-SRSLR	Right	Yes
HC24RB-4-2LL	HC24RB4C-00-PL0LR	Left	Yes
HC24RB-4-2RL	HC24RB4C-00-PR0LR	Right	Yes
HC24RB-4-3LL	HC24RB4C-00-TLSLR	Left	Yes
HC24RB-4-3RL	HC24RB4C-00-TRSLR	Right	Yes
HC24RB-4-4LL	HC24RB4C-00-RL0LR	Left	Yes
HC24RB-4-4RL	HC24RB4C-00-RR0LR	Right	Yes
HC24RO-4-1L	HC24RO4C-00-SLS0R	Left	No
HC24RO-4-1R	HC24RO4C-00-SRS0R	Right	No
HC24RO-4-2L	HC24RO4C-00-PL00R	Left	No
HC24RO-4-2R	HC24RO4C-00-PR00R	Right	No
HC24RO-4-1LL	HC24RO4C-00-SLSLR	Left	Yes
HC24RO-4-1RL	HC24RO4C-00-SRSLR	Right	Yes
HC24RO-4-2LL	HC24RO4C-00-PL0LR	Left	Yes
HC24RO-4-2RL	HC24RO4C-00-PR0LR	Right	Yes



24" C-SERIES
Refrigerator



*- Leg leveler can add 3/4" [19] to these dimensions when fully extended.

