

compromising the high quality that BBS Lighting has become known for. The FLYER is versatile by its optical design. The Integrated Soft light Diffusor creates an Omnilight with perfect light distribution.



- Lightweight Head weighs just below 1kg / 2.2 lbs
- Cool running LED Technology
- \bullet Variable color-temperature from 3000°K to 5600°K
- Full range dimmer
- Integrated Soft
 light Diffusor
- Black Out function
- Operates on Goldmount or V-Lock batteries
- Integrated Beltpack for remote controller and battery plate
- Molded transport case with room for extra accessories





FLYER Specifications

POWER

Battery operational range: 12-20V Max Power Consumption: 66W AC Power: 100-240V 50/60 Hz

LED

Premium LED configuration Stepless color-temperature adjustment from 3000°K to 5800°K At 5800°K: 6700 lm CRI 84 At 3000°K: 4400 lm CRI 93 50,000 hour life

CONTROL

Manual via remote Stepless color-temp adjustment Stepless intensity adjustment

DIMENSIONS

W: 281 mm / 11.06" H: 66 mm / 2.6" L: 281 mm / 11.06" Weight: 950 g / 2.1 lbs

These dimensions are for the head only.





THE ART OF LIGHTWEIGHT LIGHTING

THE FLYER KIT CONTAINS:

Molded case, Lamp Head, diffusor, difussor skirts, integrated beltpack, remote controller, 16' (5m) control cable, PSU, PSU power cable and a Lamp Head mount.









Lamp Head Molded case

Integrated Beltpack

16' (5m) Control Cable







Remote Controller







Lamp Head mount

Optional accessories:







Snapbag softbox

Remote extension cable









