



NEW

GALILEO TIG 219 HF



HELVI BAG XL

CE	EAC	1PH	EN 60974-1 EN 60974-10	AIR COOLING
DIRECT CURRENT DC	Connector 50mm ²	Line voltage compensation	ELECTRONIC CONTROL	DISPLAY 888
MMA	ARC FORCE	HOT START	Anti Sticking	ELECTRODES 6013 7018 Basic CrTi
TIG	Slope DOWN	HF	2T - 4T	Post GAS
Slope UP	PULSE			

HELVI CONFIGURATION KIT

GALILEO TIG 219 HF	
TIG torch	23020157 Ergotig 26 50mm ² · 4 m · 3 pin
Ground cable	43210170 25mm ² · 2 m
Helvi Bag XL	21905139
Kit Code	99806007

EN • Inverter power sources designed to meet the needs of the most demanding users. Easy-to-use both in STICK welding and TIG welding with HF start. Model 219HF: all main welding parameters can be adjusted by the user: in TIG welding, 2stroke or 4stroke mode, pre-gas, up-slope time, pulsation frequency, basic current, down-slope time, crater filler current, post-gas; in STICK welding Hot Start and Arc Force are adjustable. Equipped with digital ammeter which shows welding current and preset parameters. Model 201HF is equipped with an user friendly front panel where you can select 2T/4T, Tig slope down, MMA arc force.

IT • Generatori inverter studiati per soddisfare le necessità degli utilizzatori più esigenti. Facili da usare sia per la saldatura ad elettrodo che per la saldatura TIG con innesco con HF. Il modello 219HF permette la preimpostazione di tutti i parametri tipici di un ciclo di saldatura TIG come: modalità 2t, 4t, pre-gas, rampa di salita, frequenza di pulsazione, corrente di base, rampa di discesa, corrente di crater filler e post gas) e della saldatura ad elettrodo come: Hot start e Arc force. Dotato di amperometro digitale per la visualizzazione della corrente di saldatura e la preimpostazione di tutti i parametri. Il modello 201HF monta un frontalino semplificato con la possibilità di selezionare: 2/4T, Tig Slope down, MMA arc force.

	GALILEO TIG 219HF	
Input Voltage	(1ph) 230V 50/60Hz	
	MMA	TIG
Power 60%	5,3 KW	4,2 KW
U _o	64 V	64 V
Amp. Min-Max	10 ÷ 170 A	10 ÷ 200 A
Duty Cycle 40°C	170A @ 25% 110A @ 60% 85A @ 100%	200A @ 25% 130A @ 60% 100A @ 100%
Ø Electrode	1,6 ÷ 4 mm	-
Electrode type	6013 - 7018	-
Insulation	H	
Protection degree	IP23S	
Dimens. (LxWxH)	400x140x245 mm	
Box (LxWxH)	490x180x335 mm	
Weight box/net	8,2 / 7,7 Kg	
Code	99806005	
Dimens. in Helvi Bag XL	610x305x350 mm	
Weight in Helvi Bag XL	13,9 / 11,3 Kg	
Code in Helvi Bag XL	99806007	