

### 1. PRODUCT NAME

**Gatorfill**

### 2. MANUFACTURER

Neyra Industries, Inc.  
10700 Evendale Drive  
Cincinnati, Ohio 45241

Phone: 513-733-1000  
Toll Free: 800-543-7077  
Fax: 513-733-3989  
Email: [info@neyra.com](mailto:info@neyra.com)  
Website: [www.neyra.com](http://www.neyra.com)

### 3. PRODUCT DESCRIPTION

Gatorfill is a blend of asphalt emulsion, high molecular weight acrylic polymer, graded rubber and fine ceramic aggregate designed to fill cracks on asphalt pavement surfaces.

#### Packaging:

Available in 5 gal. pails.

#### Color:

Gatorfill dries black.

#### Basic Uses:

Gatorfill is designed as a crack filler for large cracks or minor depressions and as a mastic surface treatment for alligatored areas on asphalt pavements.

#### Composition:

As shipped, Gatorfill is a water based blend of fortified asphalt and fine graded rubber and ceramic aggregates.

#### Limitations:

Do not allow to freeze. Do not store in direct sunlight or where temperature exceeds 120°F. Do not apply if rain is imminent.

### 4. INSTALLATION

#### Preparatory Work:

Crack must be dry, clean, and free of dust and loose material.

#### Methods:

Spreadable with trowel or squeegee.

#### Mix Design:

Gatorfill is ready to use. No

- **Trowel Grade Performance:** This polymer fortified emulsion reinforced with fine aggregate provides a durable mastic for alligatored areas.
- **High Solids Formula:** High elastomeric content minimizes shrinkage in deep and/or wide cracks.
- **High Polymer Content:** Insures greater bonding, durability and flexibility.
- **Workability:** Lightweight ceramic aggregate improves spreadability for easy feathering on asphalt surfaces.
- **Fast Drying:** Repair surface imperfections in less time.
- **Convenient:** Ready to use, no mixing required.

heating or dilution is required. Stir well before use.

#### Application:

For filling deep cracks or minor depressions, a second application may be required as some shrinkage can occur. Allow a minimum of 4 hours between applications.

#### Precautions:

Keep out of reach of children. Container should be closed when not in use. Contains petroleum distillate. Avoid breathing vapor or prolonged contact with skin or eyes. Flush immediately with water. Consult specific Neyra material safety data sheet before use.

### 5. MAINTENANCE

Tools and equipment may be cleaned promptly with water.

### 6. TECHNICAL DATA

#### Environmental Considerations:

Gatorfill is considered nonhazardous when tested according to the EPA's TCLP (Toxicity Characteristic Leaching Procedure). Gatorfill is a water based material containing less than 5g/L (.08 lbs./gal.) VOC content.

### 7. TECHNICAL SERVICE

Material safety data sheets, product and application recommendations, as well as assistance with special

situations and field service are available upon request.

### 8. WARRANTY

The above specifications on product usage are believed to be true and accurate. Neyra Industries, Inc. guarantees that all materials manufactured comply with quality standards as described in the product data sheets. Because the application, handling, weather, equipment and workmanship are beyond the control of this manufacturer, only the quality of the products as shipped is guaranteed. In no case will the liability of Neyra Industries, Inc. exceed the purchase price of the shipped materials.

### 9. ADDITIONAL INFORMATION

Neyra Industries, Inc. manufactures a full line of asphalt pavement maintenance and recreational surface products as well as application equipment sold and distributed nationally at our plants and through distributors. To find the supplier most convenient to you, please contact us.

## NEYRA

Neyra Industries, Inc.  
10700 Evendale Drive  
Cincinnati, Ohio 45241  
Phone: 513-733-1000  
Fax: 513-733-3989  
Email: [info@neyra.com](mailto:info@neyra.com)  
Website: [www.neyra.com](http://www.neyra.com)