

**RVBSS – SPRAY SYSTEM
RK-SSY-0015**

PRODUCT SPECIFICATIONS

Engine Specs	-Launtop LT210 7.0HP Four-Stroke Engine with Low Oil Shutdown, Recoil Start
Pump Specs	-2" Aluminum Centrifugal Pump -Standard Duty, EPDM Mechanical Seal -Cast Iron Impeller
Tank Specs	-Add a Quick Connect Sprayer Kit to spray sealer from 55 Gallon Drums or 275 Gallon Totes (Sprayer Kit, Totes and Drums Sold Separately)
Standard Equipment	-50' x 3/4" – 275psi Rated Sealcoating Hose -6' Ball Valve Gun w Hose Swivel -2GPM, 3GPM, 4GPM Quick-Connect Spray Tips (1/Each) -Quick-Connect 3-Way Valve
Optional Equipment	-Steel Hose Reel & Mounting Bracket Kit -Line Strainer / Filter Kit -6' Squeeze Valve Gun w Hose Swivel -Sealcoating Maintenance Kit -Barrel Sprayer Kit -Tote Sprayer Kit
Performance	-Agitation occurs through pump recirculation @ 165GPM -Spraying Pressure 45psi at Tip
Weight & Dimensions	-30"x25"x30" -Weight – 120lbs

FEATURES & BENEFITS

- The Only Spray Systems built with engineered quick-connect fittings, which make assembly, disassembly, cleaning & maintenance a breeze.
- Balanced Engine Power to Pump Pressure Ratio provides optimal spray pressure while maximizing engine life expectancy
- Low Oil Shutdown prevents damage to your engine should the oil level become to low
- Quick Connect tips allow you to optimize your fan pattern, pressure and application rate without any tools
- Hose Swivel keeps spray hose tangle free during operation
- Rigid Custom-Made 3-way valve make shifting system from recirculation to spray mode a breeze
- Engineered to fit in all small to medium sized pick-ups or utility trailers