

**RYBSS – SPRAY SYSTEM
RK-SSY-0017**

PRODUCT SPECIFICATIONS

Engine Specs	- Honda GX160 5.5HP Four-Stroke Engine with Low Oil Shutdown, Recoil Start
Pump Specs	-2" Cast Iron Centrifugal Pump - Severe Duty, Viton/Tungston Mechanical Seal -Cast Iron Impeller - Stainless Steel Wear Plate
Tank Specs	-Add a Quick Connect Sprayer Kit to spray sealer from 55 Gallon Drums or 275 Gallon Totes (Sprayer Kit, Totes and Drums Sold Separately)
Standard Equipment	-50' x 3/4" – 275psi Rated Sealcoating Hose -6' Ball Valve Gun w Hose Swivel -2GPM, 3GPM, 4GPM Quick-Connect Spray Tips (1/Each) -Quick-Connect 3-Way Valve
Optional Equipment	-Steel Hose Reel & Mounting Bracket Kit -Line Strainer / Filter Kit -6' Squeeze Valve Gun w Hose Swivel -Sealcoating Maintenance Kit -Barrel Sprayer Kit -Tote Sprayer Kit
Performance	-Agitation occurs through pump recirculation @ 165GPM -Spraying Pressure 45psi at Tip
Weight & Dimensions	-30"x25"x30" -Weight – 155lbs

FEATURES & BENEFITS

- The Only Spray Systems built with engineered quick-connect fittings, which make assembly, disassembly, cleaning & maintenance a breeze
- Balanced Engine Power to Pump Pressure Ratio provides optimal spray pressure while maximizing engine life expectancy
- Powered by a Honda GX160 Four Stroke Engine with Low Oil Shutdown which provides legendary reliability
- Rigid, Cast Iron pump with Viton and Tungsten Mechanical Seals features a smaller priming cavity for easier priming and a stainless steel wear plate for a longer life expectancy when circulating semi-abrasive material.

- Quick Connect tips allow you to optimize your fan pattern, pressure and application rate without any tools
- Hose Swivel keeps spray hose tangle free during operation
- Rigid Custom-Made 3-way valve make shifting system from recirculation to spray mode a breeze
- Engineered to fit in all small to medium sized pick-ups or utility trailers