

# BE PUMP AND ENGINE

The BE Pump is an extremely lightweight pumper, powered by a four cycle air-cooled engine. This unit produces adequate pressure and volume for fire suppression, spraying and general purpose use. This smaller size pumper is particularly suited for use where water supply is limited and where weight, price and practicability are factors. This unit has a 6.5 HP Briggs & Stratton 4-cycle engine with manual recoil and an electric starter.



## SPECIFICATIONS

<b>ENGINE</b>	Briggs & Stratton 6.5HP at 3600 RPM 4 Stroke, 1 Cylinder, Air Cooled			
<b>STARTER</b>	Manual recoil and electric			
<b>SUCTION</b>	1"			
<b>DISCHARGE</b>	1"			
<b>SIZE</b>	17.5" X 15" W X 14" H			
<b>WEIGHT</b>	49 lbs.			
<b>PUMP PERFORMANCE</b>				
<b>PSI</b>	50	100	150	200
<b>GPM</b>	11	10	9	8

## REPAIR PARTS FOR BE PUMP

24019-1	Pump Head
24019-2	Housing - Rear half
24019-3	Housing - Front half
24019-4	Housing Screw
24019-5	Housing Nut (for non-CFE brands)
24019-6	Housing Gasket
24019-7	Bushing
24019-8	Impeller Guide
24019-9	Impeller
24019-10	Separator
24019-11	Impeller Guide Screw
24019-12	Shaft
24019-13	Eccentric
24019-14	Bushing Retainer Screw
24019-15	Shaft Seal
24019-16	Shaft Seal Spacer
24019-17	Gland Nut
24019-18	Locknut

