



N20-XX

## DIGIFLEX® PROFESSIONAL TOURING SERIES NXX MICROPHONE CABLES

Digiflex® Professional Touring series microphone cables represent the perfect balance between quality and ruggedness, designed to withstand the rigours of touring, delivering quality sound for years to come.

This is accomplished by using tightly twisted 24 AWG pure copper conductors with a densely woven spiral shield. Neutrik® NC3FXX and NC3MXX XLR connectors with silver-plated contacts and a rugged yet flexible outer jacket ensure the cables will perform flawlessly for years to come.

The Digiflex® NXX microphone cables are backed by a limited lifetime warranty.

### SPECIFICATIONS

**Conductor:** Two (2) 24 AWG, each consisting of 19 strands of 36 AWG pure copper

**Spiral Shield:** 95% coverage utilizing 36 AWG pure copper

**Fillers:** Cotton fillers prevent stretching and twisting of cable and ensure roundness

**Jacket:** Flexible pressure extruded PVC that remains flexible at extreme temperatures

**RoHS Compliant:** Yes

**Nominal Capacitance Conductor to Conductor:** 46 pF/ft.

**Nominal Capacitance Conductor to Shield:** 75 pF/ft.

**Nominal Conductor Resistance:** 23 Ohms/kft

**Nominal Outer Shield DC Resistance:** 8.2 Ohms/kft

**Available Lengths (ft.):** 1, 3, 6, 10, 15, 20, 25, 35, 50, 75 and 100

