

INSTALLATION INSTRUCTIONS Armorlite™ Drain Plug Sets

Vehicle Applications
Jeep Wrangler
Jeep Gladiator



CAUTION

READ BEFORE INSTALLING

- Armorlite drain plugs are designed only to work with Armorlite flooring.
- Armorlite drain plugs should not be used as replacements for the factory drain plugs if Armorlite flooring is not installed.
- Install Armorlite drain plugs in the proper locations as noted in the instructions.
- Original factory drain plugs WILL NOT FIT PROPERLY into Armorlite flooring.
- Armorlite drain plugs are engineered and designed to fit the vehicle make and model you purchased. DO NOT INSTALL in any other vehicle make or model.
- If your vehicle is serviced, check the fit of the Armorlite drain plugs to ensure they remain securely installed.

NEED SUPPORT?

Visit GoArmorlite.com/installation for detailed instructional videos & tips

View full warranty at GoArmorlite.com/warranty

Email us: Orders@GoArmorlite.com

OPTIONAL TOOLS

Not Included





Flat blade screwdriver

Pliers

INSTALLATION

1 YES



Ensure drain hole in Armorlite flooring is <u>perfectly</u> centered over sheet metal hole.

2



Open top of plug assembly.

3



Place Armorlite plug into the Armorlite floor and push into the floor of the vehicle until outer edge of the plug is fully sealed into the Armorlite surface. This requires some force to get at least 1-2 ribs on the plug to engage with your vehicle's sheet metal.

4



Place Armorlite tethered cap into the Armorlite plug until outer edge of the cap is fully seated on the outer plug rim.

OPERATION

1



To drain liquid from the Armorlite flooring surface, open the cap by pulling up on the tab opposite of the cap tether and pivoting cap up and out, if required.

2



If the cap cannot be opened by hand, a flat blade screwdriver can be used. Insert the screwdriver under the tab opposite of the tether and twist to raise the cap.

3



The plug can be removed by using pliers. Grasp and twist the crossover bar of the Armorlite plug and pull up for easy removal. <u>Do not pull plug out by cap.</u>

4

Clean any dirt or debris from plug and drain area prior to reinstalling drain plugs.