



FW-08V

8-POINT IP CONTROLLER FOR VAV

DESCRIPTION

The FW (WiFi) series supports IT network and security standards and WiFi b/g/n. This series can be used as part of an existing network or as an isolated BMS WiFi network. The dual Ethernet port capability allows for daisy chain capability within the recommended IT standards.

The FW series supports BACnet IP client/server, BACnet MSTP client, and Modbus RTU slave as well as Sox, TCOM, P2P and MQTT. The FW series also features HTML5-ready dashboards and can be programmed live via CPT. The FW-08V includes a built-in Pressure Pick-up Sensor for Air Flow Measurement used in VAV applications.

The FW-08V includes 4 UI and 4 AO. For floating control, add the optional FR-02 module. Input point capacity can be expanded with the EasyIO-FD-20i. Licenses and annual maintenance are included in the one-time cost of the controller.

FEATURES

- Pre-built VAV application with multi operation selection
- Pre-built VAV application built with BACnet variables making integration seamless
- Air Flow Balancing can be done via any HTML5 compatible web browser without any special tools
- BACnet, Modbus, TCom & Sox protocol
- BACnet MSTP Client & BACnet IP Client up to 5 devices
- BACnet IP Server over WiFi or Ethernet
- Modbus RTU Master up to 5 devices
- EasyIO Peer to Peer Protocol, compatible with FS, FG+, FW & FT Series
- Built-in web server, HTML5compatible and SSL certificate support
- MQTT, RESTful API and other web services
- Built-in dashboard
- WiFi Access Point, Repeater or Client Mode
- 2 Ethernet ports act as a normal network switch and support Ethernet daisy chain up to 9 units
- Network Time Protocol (NTP) Client
- SMTP protocol (outgoing email) with SSL authentication
- SQL Lite up to 6,000 records

TECHNICAL DATA

ITEM	DESCRIPTION
Supply Voltage	24Vac +/- 5% or 24Vdc +15% / -15%
Power Consumption	12VA
Current Rating	500mA at 24Vac / Vdc
Storage temp	-20°C to 85°C
Operating temp. range	0°C to 65°C
Operating Humidity	10% to 90% RH non-condensing
Dimensions	136 x 104 x 44 (mm)
Material	UL Approved
Weight	350g
Main Processor	MIPS 580 Mhz
Processor	ARM Cortex 48 Mhz
Flash Memory	32MB
RAM	128MB
Ethernet	2 x Ethernet Port, Non-bridged 10Base-T / 100Base-T interface, half or full duplex
WLAN	WiFi 802. 1 x b/g/n
RS 485 Ports	1 x RS485
Real Time Clock (RTC)	Real Time Clock with min. 5 days backup by SuperCAP
Network Security Standard	IPv6, DHCP Client, SSL, TLS 1.2, 802.1x, WPA Enterprise
Database and API	MQTT, SQL database, and REST API
Protocols Supported	BACnet MSTP Client, BACnet IP Client / Server, Modbus RTU Master (Modbus mode will disable BACnet Client)
Email Service	SMTP Protocol (outgoing email) with SSL authentication
Time Sync Protocol 2	Network Time Sync Protocol
Modbus Baud Rate	Speed : (9.6K, 19.2K, 38.4K, 57.6K) , Data Bits : 8 , Parity : Odd, Even, None
BACnet Baud Rate	Speed : 9.6K, 19.2K, 38.4K
Universal Inputs	4 x UI , 12-bit ADC with PGA Resistance mode : 500 – 500K Ohms (+/- 10 Ohms) Voltage Mode : 0-10V (+/- 0.05V) Pulse count mode (max) : 20 Pulse per sec at 50% duty cycle (20Hz) Digital mode : Voltage Free Contact
Analog Output	4 x AO , 12-bit DAC Maximum 5mA current draw

8 Hope St, Melrose Park, NSW 2114
(02) 9804 6366 | sales@regulatoraustralia.com.au

regulatorautomation.com.au

© Copyright Regulator Australia Pty Ltd. Due to our policy of continuous striving towards manufacturing excellence and design development, we reserve the right to change details or specifications without notice. While every effort is made to ensure accuracy at the time of publication, we shall not be held liable for any errors or omissions, implied or otherwise.

