

Valve Model	Kv	DN (mm)	Inch	Non Fail-Safe Actuators IP54				Non Fail-Safe Actuators IP66/67				
				24V, On-Off / 3-Point	24V, 2-10V Modulating	230V, On-Off / 3-Point	Close-Off	24V, On-Off / 3-Point	24V, 2-10V Modulating	230V, On-Off / 3-Point	230V, 2-10V Modulating	Close-Off
D650(NL)	90	50	2"	SR24A(-S)-5	SR24A-SR-5	SR230A(-S)-5	1200	SR24P-5	SR24P-SR-5	SR230P-5	SR230P-SR-5	1200
D665(NL)	180	65	2 1/2"									
D680(NL)	300	80	3"	GR24A(-S)-5	GR24A-SR-5	GR230A-5		GR24G-T-5	GR24G-MF-T-5	GR230G-T-5		
D6100(NL)	580	100	4"	DR24A-5	DR24A-SR-5	DR230A-5		DR24G-T-5	DR24G-MF-T-5	DR230G-T-5		
D6125(NL)	820	125	5"	DR24A-7	DR24A-SR-7	DR230A-7		DR24G-T-7	DR24G-MF-T-7	DR230G-T-7		
D6150(NL)	1600	150	6"					PRCA-S2-T	PRCA-BAC-S2-T	PRCA-S2-T	PRCA-BAC-S2-T	1400
D6200W(L)	2900	200	8"									
D6250W(L)	4400	250	10"									
D6300W(L)	7300	300	12"									1200
D6350N(L)	10900	350	14"					SY7-230A-T + ZSY-703		SY7230A-MF-T + ZSTY703		
D6400N(L)	14200	400	16"					SY7-230A-3-T + ZSY-701		SY7230-MF-T + ZSY-701		
D6450N(L)	18800	450	18"					SY8-230A-3-T + ZSY-702		SY8-230A-MF-T + ZSY-702		
D6500N(L)	24100	500	20"					SY9-230A-3-T + ZSY-901		SY9-230A-MF-T + ZSY-901		

L = Lugged, DIN16 Flanges for both wafer and lugged
 (-S) = 1 integrated auxiliary switch.
 PR and SY actuators have 2 x auxiliary switches.
 Add-on auxiliary switches for SR,GR and DR.
 S1A - single auxiliary switch, S2A - 2 auxiliary switches.
 -5, -7 = F05 (50mm) and F07 (70mm) PCD mounting.
 Fail-Safe actuators and manual valves available on request.

