


BLACKBOXMYCAR



4-in-1 Wireless Mount



Safety Hammer • Safety Belt Cutter • Gravity Mount • Wireless Charger

Device Layout

- | | |
|-----------------------|-----------------------------------|
| 1. Clip | 5. Arm Mount |
| 2. Nut | 6. Base Mount |
| 3. Safety Belt Cutter | 7. Toughened Glass Pad |
| 4. Safety Hammer | 8. Touch Sensor to Open and Close |



What's Included

- 1 x 4-in-1 Wireless Mount
- 1 x Clip
- 1 x USB A to Type C Cable
- 1 x Manual

Specification

Size: 114.97 x 70 x 104.82mm

Apply to Devices: All Mobile Device

Installation Method: Mounted

Power: 5W/10W/15W

Input: 5V/2A, 9V/2A, 12V/1.5A (Fast Charging Adapter)


Output: 5V/1A, 9V/1.1A, 9V/1.67A

Materials: Toughened Glass & Aluminum & PC & ABS


Product Use

Gravity Mount Function

Step 1: Before use, please take out the bracket and the equipped air outlet chuck, loosen the nut on the back of the bracket, install the parts together as shown in the figure, and then tighten the nut.



Step 2: After the assembly is complete, clip the mount to the air outlet of the car. Touch the sensor to open the arm mounts, and place your mobile device into the mount.




Wireless Charger Function

Step 1: Please connect one end of the Type-C cable to the USB port to connect the product.

Step 2: After the power is turned on, the white light turns on.

Step 3: To open the mount, touch panel ⑧. Put your mobile device* in the middle of the wireless charging panel ⑦ and it will be working.

**Note: The fast charge function requires a QC3.0 power adapter and the device must support the fast charge function.*



How the Safety Hammer Works


When you are **l**ocked in the car in the event of an accident, you can use the safety hammer to break the car window to escape from the car. The safety hammer ④ is hidden at the top part of the mount.

Hold the charger in your hand and break the corner of the car window where the four corners and edges of the window are the weakest.



How the Safety Cutter Works

Hold a fixed part of the seat belt with one hand and hold it tight. Then, with the other hand, hold the cutting edge against it at angle. Cut the seat belt smoothly in one direction as shown in the picture.



WARNINGS

- Do not squeeze or bump the Arm Mount
- Do not disassemble by yourself
- Do not use this product in severely high temperature, humidity or corrosive environments to avoid affecting the service life of the product
- Do not use this product as a toy to avoid accidents