

# JOYMOR

—WAGON—

# JOYMOR

—WAGON—

## Assembly & Safety Instructions



Please keep this booklet in a safe place for the life of your stroller.

## ⚠ WARNING ⚠

**Important—Keep these instructions for future reference.**

**Avoid Serious Injury To Children From Falling Or Sliding Out:**

- Always use harness to restrain each child.
- Never leave children unattended.
- Always set parking brake while loading and unloading children.
- This stroller unit is not for children under 6 months.

**Avoid Serious Injury To Children:**

- Use with caution when pushing stroller near traffic or in highly congested areas.
- DO NOT use stroller on stairs or escalators with children in it.
- To avoid injury, ensure that your child is kept away when unfolding and folding this product.
- Do not let your child play with this product.
- This product is not suitable for running or skating.

**Avoid Injury From Stroller Tipping Over:**

- DO NOT carry more than two (2) children.
- DO NOT exceed per seat limit: 33 lbs.
- DO NOT place any child taller than 40 inches per seat in this stroller.
- DO NOT allow children to climb into stroller unassisted, or to play or hang onto stroller.
- DO NOT overload stroller as it can become unstable.
- DO NOT add package carrying accessories or hang items from stroller. Parcels or accessories which are not approved by the manufacture placed on the unit may cause the unit to become unstable.
- DO NOT place more than 11 lbs. (5 kg) in storage pocket.
- ALWAYS distribute weight as evenly as possible on each side of the stroller.

**Avoid Loss Of Control Of Stroller:**

- Ensure that all the locking devices are engaged before use.
- NEVER leave stroller unattended on a hill or incline even when parking brake is set.
- Use with caution when pushing stroller on uneven terrain or slopes.
- ALWAYS set parking brake when the stroller is stationary.

**Avoid Pinch Injury:**

- Keep fingers clear of hinged joints when folding and unfolding the stroller.
- When making adjustments, always ensure all children are kept well away from any moving parts.

**See instructions for additional warnings and use all information.**

## Parts Check List

			
1. Stroller Body	2. Rear Wheels×2	3. Front Wheels×2	4. Seat Unit×2
			
5.Canopy	6. Handle Bar with Screws	7. Brake Bar Set	8. C-Shape Buckle (located on the brake bar)
			
9. Optional Strap (located in the front pocket)	10.Carriage Bag	11.Matress	

## Assembly

### Unfolding the Stroller

1. Stand with hands on front and rear frame tube, and unfold the stroller frame to front and rear position.
2. Stretch out the fabric flaps to both sides of the hand rail to cover the joint on both sides.



### Assembly of Front Wheels

1. Insert front wheels into front wheel housing.
2. Front wheel assembly completed. Pull the front wheel to be certain that wheels are securely locked in place.



### Assembly of Rear Wheels

1. Insert the wheel axle in the brake assembly as picture 1.
2. Insert the buckle into the rear wheel housing as picture 2. Pull the rear wheel axle to make certain that rear wheel assembly is secure.



### Assembly of Rear Wheels

1. Connect the rear wheel to the rear tube joint.
2. Check the clips are in place on both sides of the wheel housing.



### Assembly of Handle Bar

1. Screw the handle bar tube to the adjust joint using screws.
2. Tighten the screws on both sides.



### Matress Assembly

Lay the mattress flat on the bottom of the stroller





## Seat Assembly (seat is suitable for children from 6 to 36 months)

1. Place the seat into one end of the stroller.
2. Fix the hooks on both sides of the seat onto the hand rail of the stroller frame.
3. Fix the buckle on back of the seat onto the connect tube of the stroller frame.
4. Repeat on the other end to assemble the other seat.

1



2



3



## Canopy Assembly

1. Connect the canopy tube to the rail on four corners.
2. Assembly of canopy is finished.

1



2



## Installation instructions For the Carriage Bag:

Insert the tube on the bag into the tube of the wagon

1



2



## Handle Strap Assembly

1. Take out the handle strap from front pocket of the frame.
2. Fix the handle strap onto the front connecting tube.
3. Use as shown in picture 3.

1



2



3





## Operation

### Securing the Harness

1. With harness unbuckled, place child in seat.
2. Secure child with harness by placing shoulder and waist belts over shoulders and over thighs. Snap buckle tongues into crotch strap buckle.
3. Snugly adjust each strap by pulling on the free end of the strap and moving the slide adjuster along strap.
4. Fasten the button on the protective cover of the safety harnesses.



1



2



3



4

### Parking Brake Operation

1. Step down on the parking brake pedal to lock. Test the brake to ensure it's locked by trying to push the stroller.
2. Push the parking brake pedal upwards with your foot to release it.



1




2

### Adjustable handle

1. Press the adjustable handle button on both sides simultaneously.
2. Move handle up or down to desired height.



1



2

## Canopy Storage

1. Roll up the canopy fabric.
2. Adjust the handle bar to upright position.
3. Hang the canopy tube onto the handle-bar and insert one end of the canopy tube into the pocket in the storage basket.
4. Secure the strap on the rear tube with the buckle.



1



2

## Cleaning

### Cleaning Stroller

1. Wash stroller frame with mild soap and water.
2. Rinse and wipe or air-dry.

### Cleaning Seat Pad

1. Spot clean with mild soap and water.
2. Rinse and wipe or air-dry.

Thank you for your purchase. Please contact us if you have any difficulty with assembly or need replacement parts. JOYMOR Customer Service is here to assist you. Email Address:

support@joymor.com

Please attach your Order ID so that we can assist you better.