

- Remove:** Seat (2 allen bolts under corners) and seat cowl.
- Remove:** Left and right side trim (13 allen bolts). *FIG(A)
- Remove:** Upper tail section (4 allen bolts). *FIG(B) Unplug tail light and signal flasher.
- Remove:** Exhaust cans (1 bolt & 1 spring each).
- Remove:** Rear fender (3 allen bolts to remove coverplate in back of fender *FIG(C) 2 bolts to remove fender)*FIG(D) Unplug wires *mark left & right turn signal wires on bike.
- Remove:** Fender mounting block (4 nuts)*FIG(D) Pull all stock wiring up through underside of tail section.
- Apply:** Supplied Lic light to werkes license pan. Cut off bullet connectors on lic light, slide on supplied conduit, cut stock plug off stock license light, *leave about 6" of wire. Connect plug to supplied lic light using supplied butt connectors (connect black to white, blue to black). *FIG(E)
- Next:** Bolt lic pan to mounting block *leave loose. Use stock bolts. Feed lic light plug through mounting block and through underside of tail section. Re-install mounting block to bike.
- Adhere:** Supplied turnsignal lights to turnsignal brackets. *FIG(F) Cut stock signal plugs off *leave about 6" of wire. Connect to supplied turn signals with supplied butt connectors.
- Adhere:** Turn signal brackets to the inside of the tail section *FIG(G).
- Plug-in:** All wiring (tail light, turn signals, & turnsignal flasher) *CHECK ALL LIGHTING
- Re-install:** Tail section, side trim, & exhaust. Then align lic pan & tighten bolts.

PARTS LIST:

- | | |
|-------------------------|---------------------|
| 1- License Pan | 4- 6x10 Allen Bolts |
| 2- Turn Signal Brackets | 4- Washers |
| 1- License Light | 4- 6mm Nuts |
| 1- Pair Flush Mounts | 6- Butt Connectors |
| | 1- 6" Conduit |

07 Ducati 1098
Fender Eliminator

