

<>>>>> A QUALIFIED TECHNICIAN

REMOVE: Seat. (1-allen bolt, pull back and off)

REMOVE: Rear fender. (4-bolts on underside, unplug wiring)

REMOVE: Cover of Tail Light Spoiler. (1-allen bolt)

REMOVE: Tail Light Spoiler. (4-bolts, unplug wires)*FIG (A)

PULL: Stock signal wires up into seat area.

ADHERE: Signals to Signal Brackets.*FIG(B)

POSITION: Tail Light Spoiler and Turn Signals. (Align signals, and

secure with stock bolts)

ROUTE: Wiring as desired and plug in. (secure with zip ties)

MOUNT: License Light Bracket. (secure with 2 rear bolts)*FIG(C)

ADHERE: License Light.

MOUNT: License Pan. (2-forward bolts)*FIG(C)


CONNECT: License Light wires. (use supplied Butt Connectors, route


as desired and secure with zip ties)

MOUNT: License Plate. (4-3/8" Pan Screws)

CHECK: Lighting for proper functions.

REPLACE: Spoiler cover and seat.











PARTS LIST:

- 1- License Light Bracket
- 1- License Pan
- 1- License Light
- 1- Pair Flush Mount Signals
- 1- Pair Signal Brackets
- 4- 3/8" Pan Screws
- 4- 1/4" Nuts
- 4- Washers
- 4- Small Zip Ties
- 2- Butt Connectors