



<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

**(800)736-2114**

## Ducati Hypermotard Limited Fender Eliminator

- REMOVE: Seat.
- UNPLUG: Stock signals and license light. \*FIG (A)
- REMOVE: Rear fender. (4-allen bolts).
- CUT: Wires as shown in \*FIG (B). \*NOTE\* Identify and mark wire for future reference.
- ADHERE: License light to Main Pan. \*FIG's (C) (D) & (E) for assembly next several steps.
- SECURE: License plate to License Pan (use 4- 6x10mm allen bolts, washers, and nuts).
- ADHERE: Signals to Main Pan. Route wires as shown.
- CONNECT: All wiring using connectors provided. Check lighting for proper function.
- SECURE: Assembly to undertail (use 4- 8x12 allen bolts).
- REPLACE: Seat.

### PARTS LIST:

- 1- Main Pan
- 1- License Pan
- 1- License Light
- 1- Pair Flush Mount Signals
- 4- 8x12mm Allen Bolts
- 4- 6x10mm Allen Bolts
- 4- Washers
- 4- 6mm Nuts
- 2- Butt Connectors



The purchaser releases Competition Werkes Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.

1DHYP2LTD

# COMPETITION WERKES

<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

(800)736-2114



The purchaser releases Competition Werkes Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.

1DHYP2LTD