

## 02 VFR 800 FENDER ELIMINATOR KIT INSTRUCTIONS:

**CAUTION:** STAINLESS STEEL EDGES CAN BE SHARP!

1. REMOVE SEAT, TOOL KIT, OWNERS MANUAL.
2. REMOVE FENDER, 4 BOLTS IN STORAGE AREA, 2 BOLTS ON UNDERSIDE. REMOVE 2 NUTS ON BACK OF LICENSE LIGHT, UNPLUG LICENSE LIGHT AND REMOVE.
3. MOUNT FENDER PAN WITH 2 STOCK BOLTS ON UNDERSIDE. (CENTER PAN BETWEEN MUFFLERS BEFORE TIGHTENING).
4. ATTACH LICENSE PLATE LIGHT TO FENDER PAN USING THE 2 - 4mm NUTS SUPPLIED. THIS IS A TIGHT FIT, YOU MIGHT NEED TO PUSH PAN BACK IN ORDER TO GET NUTS STARTED. RUN WIRE UP THRU ONE OF THE HOLES IN BLACK PLASTIC FENDER. INSTALL PLUGS IN THE THREE REMAINING HOLES. PLUG IN THE LICENSE PLATE LIGHT. MOUNT LICENSE PLATE AND THEN CHECK LIGHTING FOR PROPER OPERATION.
5. REPLACE TOOL KIT, OWNERS MANUAL AND SEAT.

**PARTSLIST:** 1- Fender Pan, 3- Small Plugs, 2- 4m Nuts, 4- 6m Nuts, 4- Washers, 4- 6x10 Allen Bolts

TOP VIEW - REMOVE 4 BOLTS



UNDERSIDE

