

1K607



- Remove: Small trim piece above tail light (2 plastic rivets by pushing center in).
- Remove: Turn signals (three allen bolts)*FIG(A) from both sides. Cut wires mark for identification.
- Remove: Stock Signal mounts (2 allen bolts each side).
- Remove: Rear fender from exhaust (4 - 10mm bolts).
- Remove: Tail light from rear fender.
- Cut: Wires to lic light & tail light (close to the lights).
- Remove: Bracket from tail light.
- Mount: Supplied turn signals to main pan.
- Mount: Lic light to lic pan.
- Secure: Lic pan & tail light to main pan, with stock tail light screws.
- Insert: All hanging wires on bike through SS conduit
- Insert: Conduit through large hole on back of main pan.
- Connect: All wires to corresponding lights, using butt connectors.
- Mount: Main pan to exhaust (4 allen bolts).
- Check: All lighting for proper function.



Parts List:

- | | |
|------------------------|---------------------|
| 1 - main pan | 9 - butt connectors |
| 1 - lic pan | 1 - lic light |
| 4 - 6 x 12 allen bolts | 1 - pair signals |
| 4 - washers | 1 - lg conduit |
| 4 - nuts | |

07 KAWASAKI ZX-6R FENDER ELIMINATOR