

SUZUKI SV650 INSTRUCTIONS

CAUTION: STAINLESS STEEL EDGES CAN BE SHARP!

1. REMOVE SCREWS HOLDING BLACK SIDE COVERS BELOW GAS TANK AND SWING TO THE SIDE.
2. REMOVE SEATS AND HANDRAIL.
3. REMOVE TAIL SECTION, 6 SCREWS ON TOP, 2 UP UNDERNEATH ABOVE TURN SIGNALS AND 2 SMALL SCREWS AND CLIPS HOLDING SIDES OF TAIL SECTION TOGETHER. DISCONNECT SEAT LATCH CABLE AT KEY LOCK.
4. REMOVE TURN SIGNALS AND TAIL LIGHT, UNPLUG WIRES. UNSCREW BLACK IGN. BOX AND MOVE ASIDE.
5. MAKE CUTS AS SHOWN, START WITH SIDE CUTS FIRST CUTTING FROM FRONT TO BACK. THE BLADE OUT OF A HACKSAW WORKS WELL, OR MOST ANY CUTTING TOOL. TAKE YOUR TIME, NOTE DIAGRAMS, WATCH WIRES.
6. SET TAIL SECTION BACK IN PLACE (BE SURE IT'S SEATED DOWN ON THE REAR GROMMETS) SET INNER FENDER IN PLACE AND INSTALL THE 2 SCREWS YOU REMOVED (DON'T TIGHTEN, THIS IS ONLY TO LINE THE HOLES UP) DRILL UP THROUGH THE 2 REARMOST HOLES WITH A 1/4" DRILL AND INSTALL 2 TRUSS HEAD SCREWS WITH WASHER AND NUT ON TOP ONLY. CAREFULLY REMOVE TAIL SECTION AND DRILL OUT THE REMAINING 4 HOLES. MOUNT THE 2 SIGNAL BRACKETS AND LICENSE PAN USING 4 BOLTS WITH WASHERS ON EACH SIDE AND NUTS ON TOP. NOTE: SIGNAL BRACKETS CAN BE MOUNTED ON EITHER SIDE WHICH WILL MOVE SIGNALS IN OR OUT FARTHER. INSTALL 2 GROMMETS TO RUN WIRES UP THROUGH. REMOVE CONNECTOR FROM STOCK LICENSE PLATE LIGHT AND CONNECT TO NEW LIGHT WITH RED CONNECTORS. PUSH LIGHT UP INTO PLACE AND MOUNT LICENSE PLATE. REMOVE THE 2 SCREWS ALONG WITH CLIPS THEY THREADED INTO.
7. REROUTE WIRE HARNESS FROM BLACK BOX TO GIVE YOU ENOUGH SLACK TO REMOUNT WHERE THE TOOL POUCH WAS. BY TUCKING WIRES UP ON TOP THE STRAP WILL FIT TIGHT. THE OTHER OPTION IS TO DRILL 2 HOLES AND MOUNT ELSEWHERE.
8. REPLACE TAIL LIGHT AND CONNECT ALL WIRES (GREY LEFT SIGNAL, BLACK RIGHT SIGNAL). REATTACH SEAT LATCH CABLE AND THEN CAREFULLY REMOUNT TAIL SECTION. INSTALL PLASTIC RIVETS WHERE THE 2 SCREWS WERE (EXTEND THE RIVIT THEN PUSH IN PLACE.)
9. MOUNT TURN SIGNALS USING LARGE WASHER PROVIDED ON THE INSIDE, RUN WIRES UP THROUGH GROMMETS AND CONNECT. CHECK ALL LIGHTS FOR PROPER OPERATION. MOUNT HANDRAIL AND SEATS.

PARTS LIST: INNER FENDER, LICENSE PAN, 2 SIGNAL BRACKETS, LICENSE PLATE LIGHT, 2 1/4X5/8 TRUSS HEAD SCREWS, 2 PLASTIC RIVETS, 2 SCREWS, 4 1/4X5/8 BOLTS, 8 NUTS, 12 WASHERS, 2 LARGE WASHERS, 2 CONNECTORS.

