

02 Triumph Daytona/Speed Triple

- 1) **REMOVE**, these parts from Fig A to end up with Fig C. [rear seat or cowl, front seat (2 bolts in storage area), Tail Section (6 – allen screws on tail, 2 allen screws on side panels, 2 rivets on bottom and lower clip on center splice)]
- 2) **REMOVE**, these parts from Fig C to end up with Fig D. [tail light w/mount (3 allen screws in mount, unplug wires), tail light surround (2 – allen screws on sides), license plate mount (3 – allen screws, unplug wires), turn signals (2 – lg nuts, unplug wires), reflectors (drill out rivets, set one reflector aside for later)]
- 3) **CUT**, using hacksaw blade make cuts to Fig D to end up with Fig E. Make sure to leave two mounting points in tact! Smooth all cuts w/sand paper or file so bottom is flush and mounting points are clear – make a 1”x1” notch out of center between mounting points.
- 4) **REMOVE** cover from license light (2 small screws). Mount backing plate with bulb to license light mount (keep tight to the window). Insert reflector into back of license light mount.
- 5) **MOUNT** license light mount and license plate mount to mounting points at rear of frame (use 2 stock bolts & 2 supplied washers. License plate mount must be up as high as possible, while the license light mount should be as low as possible. Plug in wires)
- 6) **INSTALL** tail light surround (use 2 plastic rivets supplied) Fig F.
- 7) **INSTALL** tail light (3 stock allen screws, plug in wires) Fig G.
- 8) **MOUNT** body work (make sure tail light surround is inside the body work and partial insert 2 plastic rivets supplied) secure with stock fasteners (6 allen screws on tail, 2 allen on side panels, lower clip at splice).
- 9) **POSITION** fender panel (slide panel between inner fender/tail light surround and bodywork, align w/back of license plate mount) secure w/2 self drilling screws provided and full insert the plastic rivet. Repeat on other side. Insert rubber grommet.
- 10) **MOUNT** turn signals to signal brackets. Run ½” screws through license plate, license mount and signal brackets. Put a washer & nut on back, position & secure! Run wires up through grommet and connect w/red connectors supplied.

<u>h wiring”</u>	<u>“Supplied signals”</u>	<u>“Triumph</u>
= ground	Black w/white = ground	Black
= license light	Red or Black = postive	Yellow
Green/White = right turn		
Green/Red = left turn		
- Align signals as desired, check for proper installation. Replace seats or cowlng.		
- 11) **POSITION** battery box cover & secure w/2 self drilling screws.

PARTS LIST: 1 license light mount w/window, 1 license plate mount, 2 fender panels, 1 battery box cover, 2 signal brackets, 1 set of signals, 4 ½” screws, 4 nuts, 6 washers, 4 plastic rivets, 6 self drilling screws, 4 connectors, 1 grommet

TRIUMPH SPEED TRIPLE/DAYTONA

