

'03 YAMAHA YZF 600 R-6

- REMOVE:** Rear seat
- LOWER:** Rear fender (4 allen screws in storage area FIG B)
- LOWER:** Undertail (8 plastic rivets on underside) *Carefully pry down w/a small flat head screwdriver
- UNPLUG:** Right & left turn signals and license light. Reroute wire up into storage area. (FIG'S C & F) Set fender aside.
- INSTALL:** 2 ex-large washers to sleeves on bottom. (FIG F)
- REINSTALL:** Undertail (8 plastic rivets) careful not to knock washers off of sleeves.
- INSTALL:** Signal mount (2 – 6x25 Allen Bolts up through w/a washer & nut on top. Then drill up through oblong holes w/a ¼” drill bit, angle back towards the tail as photo shows. (FIG D) *It may be necessary to enlarge these holes from the opposite side of signal mount.
- INSTALL:** Turn signals - run wires through drilled holes. (Use large hole in undertail as an access to guide wires into storage area through rectangular openings. (FIG'S F & G)
- INSTALL:** License Plate Mount (2 – 6x30 Allen Bolts up through, w/3 large washers and the stock spacer on top, secured w/a small washer and nut)
- INSTALL:** License Light Mount (2 – 6mm Nylo nut w/small washers. FIG G)
- DISASSEMBLE:** Stock License Light (FIG E) Drill ½” hole in plastic (if ½” drill bit is n/a you can heat up the ½” tube and push through plastic) Insert into license light mount (FIG G) *Bulb should not be touching metal
- CONNECT:** ALL WIRING (Use supplied connectors to splice ends off your stock signals FIG G)
- INSTALL:** License Plate (4 – 6x12 Allen Bolts)
- LOCATE:** Contents of storage area so as not to affect license light
- CHECK:** Lights for proper operation
- REPLACE:** Seat

***CONTENTS:** License plate mount, turn signal mount, license light mount, turn signals, 2 xl washers, 6 lg washers, 10 sm washers, 2 – 6x30 Allen Bolts, 2 – 6x25 Allen Bolts, 4 – 6x12 Allen Bolts, 1 – ½” tube, 4 connectors, 10- 6mm Nyloc Nuts



YAMAHA R-6

