

PARTS LIST:

1- Canister 1- Mid-pipe

1- Spring 1- 2.25 Clamp

1- Mounting Bracket 1-8x25 Bolt

1-8mm Washers 1-8mm Nut 2-6x30 Bolt 2-6mm Washer 2-6mm Nut

<><<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>:

(800)736-2114

Aprilia RSV4/Tuono slip-on exhaust

1) Remove stock exhaust canister. (1-bolt, 1-clamp)

- 2) Remove upper bolt from heal guard. *See side image.
- 3) Position supplied Mounting bracket behind the heel guard and rear brake piston and loosly secure with supplied 6x30 allen bolt/washer/nut.
- 4) Remove lower bolt of heal guard and replace with 6x30 allen bolt/washer/nut to finish installation of Mounting Bracket.
- 5) Position Mid-pipe onto and loosly secure with supplied Clamp.
- 6) Install WerkesUSA canister using supplied Spring and hardware.
- 7) Wipe exhaust down with WD-40 (or similar) to remove any fingerprints or grime.





The purchaser releases Competition Werkes Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.