



<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

**(800)736-2114**

## 2011-2014 Honda CBR250r GP Exhaust

- REMOVAL:
- 1) Remove large stock heat shield (1- allen bolt, slide rearward).
  - 2) Remove small stock heat shield (1- allen bolt, slide rearward).
  - 3) Remove stock exhaust canister (1- bolt at rear peg, 1 clamp). Remove gasket.
- INSTALL:
- 1) Install WerkesUSA GP Exhaust using supplied clamp.
  - 2) Adjust for swingarm and brake lever clearance. Tighten clamp securely.
  - 3) Clean exhaust of fingerprints and grime using WD-40 (or similar).

### PARTS LIST:

1- GP Exhaust Canister 1- 1 5/8" Clamp

**\*\*IMPORTANT\*\*** To insure uniform coloring thoroughly clean with WD-40 or like product before starting motorcycle **\*\*IMPORTANT\*\***



The purchaser releases Competition Werkes Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.

WH250-S