



06-07 KAWASAKI ZX10R SLIP ON EXHAUST

<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

REMOVE: Side covers located below front seat. (One allen bolt near tank on each side. Pull off from bottom and rear)

REMOVE: Front and rear seats.

LOOSEN: Tail section. (Remove 4-allen bolts near rear seat, 2 push rivets near front seat, and 4 push rivets in underside)
NOTE- to remove push rivets. Simply push center pin in 1/8", then pull out on outer ring. Reset rivet by pushing pin back out 1/4" before reusing.

LIFT: Tail section and slide it back enough to expose exhaust mounting bolts. (leave all wiring and cables connected)

REMOVE: Heat shield from right side of subframe.

REMOVE: Stock exhaust canisters.

REMOVE: Stock "Y" pipe.

REMOVE: Undertail heat shield. (bolts can be reinstalled to fill holes)

REMOVE: Lower side panel on right side.

INSTALL: Mounting Bracket behind rt. heel guard using stock bolts (leave loose).

INSTALL: WerkesUSA exhaust canister at stock location with supplied stainless steel clamp, and secure to Mounting Bracket with supplied bolt, washers and nut. Tighten heel guard bolts.

ALIGN: Lower side panel and trim as desired.

REPLACE: Side panel, tail section, seats, and side covers using stock hardware.

CLEAN: Exhaust before starting.

****IMPORTANT**** To insure uniform coloring thoroughly clean with WD-40 or like product before starting motorcycle ****IMPORTANT****

PARTS LIST:

- 1- WerkesUSA Canister
- 1- Mounting Bracket
- 1- Stainless Steel Clamp
- 1- 8x25 Allen Bolt
- 1- 8mm Nut
- 2- Washers



The purchaser releases Competition Werkes inc from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.