



<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

(800)736-2114

Kawasaki

2011-15 Ninja 1000

2014-15 Z1000



REMOVAL:

- 1) Remove seat/seats
- 2) Remove cables to exhaust valve by removing servo head (T-27 bolt) and retaining clip *FIG (A). Feed cables through frame.
- 3) Remove rear bolt from head shield on right side. *FIG (B)
- 4) Remove stock canisters (1 bolt, 1-clamp per side).

INSTALL:

- 1) Install Mounting Brackets to rear footrests (use stock hardware leave loose). *FIG (B)
- 2) Install WerkesUSA Canisters (use stock gaskets and clamps. Supplied 8x16 allen bolts, washers, and nuts). See *FIG (B).
- 3) Align Canisters and tighten all hardware and clamps.
- 4) Replace bolt in head shield.
- 5) Clean exhaust with WD-40 (or similar product).
- 6) Install seat/seats.

PARTS LIST:

2- WerkesUSA Canisters 2 Mounting Brackets 2- 8x16 Allen Bolts 2- 8mm Nuts 4- 8mm Washers

****IMPORTANT**** To insure uniform coloring thoroughly clean with WD-40 or like product before starting motorcycle ****IMPORTANT****



The purchaser releases Competition Werkes Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.

WK1002-S