



<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

(800)736-2114

Kawasaki Ninja 300

- REMOVE: Stock exhaust heatshield (1-allen bolt, loosen clamp, slide forward and off).
- REMOVE: Stock exhaust (1-bolt/nut at passenger footrest, loosen clamp). ****NOTE**** footrest mount will not be reused. either remove footrest entirely or remove bushing to store with stock exhaust.
- INSTALL: WerkesUSA GP Canister using supplied clamp. Push canister forward until you feel the mid-pipe touch the inside of canister. Then pull back 1/8". Adjust to desired angle, check swingarm clearance, tighten clamp securely. ****NOTE**** it is very important that you check clamp periodically for tightness.
- INSTALL: WerkesUSA Heatshield (use stock clamp, and supplied 6x10 allen bolt).
- CLEAN: Canister of fingerprints or smudges with WD-40 or similar product before starting. This will insure color fastness.

****NOTE**** This exhaust was design with the exhaust insert installed. REMOVING INSERT WILL REQUIRE RE-JETTING!!!!

PARTS LIST:

1- WerkesUSA GP Canister 1- WerkesUSA Heatshield 1- 1 5/8" Clamp 1- 6x10mm Allen Bolt



****IMPORTANT**** To insure uniform coloring thoroughly clean with WD-40 or like product before starting motorcycle ****IMPORTANT****

The purchaser releases Competition Werkes Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.

WK300-S