



<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

(800)736-2114

# Kawasaki

Ninja 400 GP Slip-on

- 1) Remove stock exhaust heat shield (1- bolt, 1- clamp, slide forward).
- 2) Remove stock exhaust canister (1- bolt, 1- clamp).
- 3) Remove clamp from stock exhaust.
- 4) Remove gasket from stock exhaust (carefully bend inlet open to release pressure from gasket).
- 5) Install stock gasket into WerkesUSA GP Exhaust in et.
- 6) Install WerkesUSA GP Exhaust using stock clamp and hardware.
- 7) Install supplied Heat Shield with 6x10 allen bolt and stock clamp.

PARTS LIST:

1- GP Canister    1 Heat Shield    1- 6x10 Allen Bolt



**\*\*IMPORTANT\*\*** To insure uniform coloring thoroughly clean with WD-40 or like product before starting motorcycle **\*\*IMPORTANT\*\***

The purchaser releases Competition Werkes Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.

WK400