



<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

(800)736-2114

YAMAHA R3

GP Slip-on Exhaust

- REMOVAL:**
- 1) Remove stock exhaust canister (1- bolt and 1- clamp)
 - 2) Remove stock side heat shield (3- allen bolts near rider right rearset).
 - 3) Remove stock side heat shield mounting bracket (2 bolts).
- INSTALL:**
- 1) Install supplied heat shield mounting bracket (use stock bolts).
 - 2) Install WerkesUSA Exhaust Canister (stock bolt/nut, clamp, and supplied gasket).
 - 3) Install WerkesUSA Heat Shield (use 2- supplied 6x12 allen bolts).

PARTS LIST:

1- GP Exhaust Canister 1- Heat Shield 1- Heat Shield Mounting Bracket 2- 6x12 Allen Bolts 1- Gasket

****IMPORTANT**** To insure uniform coloring thoroughly clean with WD-40 or like product before starting motorcycle ****IMPORTANT****



The purchaser releases Competition Werkes Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.

WY300-S