



<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

(800)736-2114

Yamaha YZ-R6

GP Slip-on Exhaust

- 1) Remove front seat (2- allen bolts under corners).
- 2) Remove lower fuel tank shrouds (1- bolt per side, carefully slide rearward)
- 3) Unbolt fuel tank at rear and sides (lift and support).
- 4) Remove cross brace under rear of fuel tank.
- 5) Remove heat shield from stock exhaust canister
- 6) Remove Ex-up cables from exhaust.
- 7) Remove exhaust canister.
- 8) Remove Ex-up cable clamp from right side rearset.
- 9) Remove Ex-up cables from cable harness behind rear brake fluid reservoir.
- 10) Remove Ex-up motor (unplug electrical connector and pull motor and cables out the top).
- 11) Remove cable cover from Ex-up motor.
- 12) Remove cables.
- 13) Reinstall Ex-up motor (without cables) into bike and plug in electrical connector.
- 14) Reinstall cross brace under rear of fuel tank.
- 15) Reinstall fuel tank, tank shrouds, and front seat.
- 16) Install WerkesUSA exhaust canister using supplied clamp, stock bolt, supplied washer, and supplied 8mm nut.
- 17) Clean canister with WD-40 (or similar) before starting.

****IMPORTANT**** To insure uniform coloring thoroughly clean with WD-40 or like product before starting motorcycle ****IMPORTANT****



PARTS LIST:

- 1- Canister
- 1- 1.75" Clamp
- 1- 8mm Washer
- 1- 8mm Nut

The purchaser releases Competition Werkes Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.

WY610B