

PARTS LIST:

- 1- GP Canister
- 1- 8mm Nut
- 1- 8mm Washer
- 1- 2 1/8" Clamp



Yamaha
FZ-09/FJ-09/XSR900
slip-on exhaust

<<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

(800)736-2114



****IMPORTANT**** To insure uniform coloring thoroughly clean with WD-40 or like product before starting motorcycle ****IMPORTANT****

REMOVE: Stock exhaust (2- bolts above canister, 6- head nuts, 1- O2 sensor (let hang)) *FIG (A)
*NOTE Remove center stand on FJ-09 (2- bolts, 1- spring)

CUT Head pipe where shown in *FIG (B) using a die-grinder with a cut-off wheel, or Sawzall/hacksaw, with a bi-metal blade. *NOTE* If you don't feel confident doing this please take to a qualified technician.

GRIND: Cut clean using a 5" air-sander (recommend 36 grit) or angle grinder. *FIG (C)

REINSTALL: Head pipe (6- nuts).

INSTALL: WerkesUSA canister and clamp. Use a bead of high-temp silicone at joint for a good seal. Use a stock bolt and supplied 8mm Nut. *IMPORTANT* Use supplied 8mm Washer between mount and chassis.

ADJUST: Clearance and tighten all hardware. Replace O2 sensor. Clean entire exhaust with WD-40 before starting.
NOTE Replace center stand on FJ-09.

The purchaser releases Competition Werkes Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident, and may also render the vehicle illegal for use on public roads.

WY900-S