

Core Line SIZING AND SPECS





SIZES

SMALL (50 CM)	Riders 5'4" - 5'7"
MEDIUM (54 CM)	Riders 5'7" - 5'11"
LARGE (58 CM)	Riders 5'11" - 6'2"

COMPONENTS AND FRAME GEOMETRY

1 Brakes	Front and rear brakes pre-installed
2 Frame & Fork	Durable Steel with 5 year warranty
3 Handlebars	Riser Handlebars with VANS Grips
4 Pedals	Plastic platform pedals
5 Tires	25c Kenda Tires for a smooth ride
6 Wheels	40mm Deep V Style Rims

DETAILED SIZING AND SPEC GUIDE

	46cm	50cm	54cm	58cm
ACTUAL TOP TUBE LENGTH	499mm	513mm	537mm	554mm
BB DROP	50mm	50mm	50mm	50mm
BB HEIGHT	268.5mm	268.5mm	268.5mm	268.5mm
CHAIN STAY LENGTH	405mm	405mm	405mm	405mm
COMPLETE BIKE WEIGHT	11,406g	11,580g	11,740g	11,870g
CRANK ARM LENGTH	170mm	170mm	170mm	170mm
EFFECTIVE TOP TUBE LENGTH	513mm	522mm	538mm	555mm
FORK LENGTH	402mm	402mm	402mm	402mm
FORK OFFSET	45mm	45mm	45mm	45mm
HEAD TUBE ANGLE	71.5°	72°	71°	73°
HEAD TUBE LENGTH	105mm	105mm	105mm	135mm
REACH	368mm	374mm	380mm	386mm
SEAT TUBE	460mm	500mm	540mm	580mm
SEAT TUBE ANGLE	74°	74°	73°	73°
STACK	508mm	522mm	536mm	570mm
STANDOVER HEIGHT	733mm	751mm	775mm	811mm
WHEEL BASE	975mm	985mm	989mm	1003mm

DETAILED SIZING AND SPEC GUIDE

BOTTOM BRACKET

Sealed Cartridge
JIS Square Taper
English Threaded
68mm x 103mm

BRAKES

Dual Pivot
Forged Alloy
Clamp Diameter: 23.8mm

CHAIN

YAB Chain

CHAINRING

44T
130 BCD

CRANK

Forged 6061 Aluminum
Crank Arm Length: 170mm

FORK

Hi Tensile Steel
1 $\frac{1}{8}$ " threadless steerer

FRAME

Hi Tensile Steel

HANDLEBARS

Aluminum
Bullhorn: 420mm
Drop: 450mm
Riser: 570mm

HEADSET

1 $\frac{1}{8}$ " threadless

HUBS

Sealed Bearing, Flip-Flop Hub
16T Freewheel and Fixed Cog
Spacing: F: 100mm / R: 120mm
Bolts: F: M10 / R: M10

PEDALS

Plastic Platform Pedal

SADDLE

Polyurethane
Steel Rails

SEAT POST

Alloy
Diameter: 27.2mm
Length: 300mm

SEAT POST CLAMP

Aluminum
Diameter: 29.5mm

SPOKES

14G Stainless Steel, 3 Cross Pattern
Spoke Length F/R: 269mm

STEM

Steel
Clamp Diameter: 25.4mm
Length: 90mm
Rise: +/- 7°

TIRES

Kenda Brand
700c x 25mm
Suggested Max Tire: 28mm

WHEELS

700c Aluminum Wheel Set
Rim Depth: 40mm