

Undeclared Track

SIZING AND SPECS





COMPONENTS

| | |
|-------------------------|---|
| 1 Bottom Bracket | BSA (English) BB |
| 2 Chain | KMC K710 |
| 3 Crankset | Essor Aerodash 7075 AL CNC 48T chainring 170mm |
| 4 Fork | Full Carbon with Carbon Steer Tube, 340g, 45mm rake |
| 5 Frame | Double Butted Y9 Kinesium Aluminum Alloy, w/ Tapered Headtube (1 ¹ / ₈ " x 1 ¹ / ₂ " |
| 6 Handlebars | State 42mm Track Drop bars |
| 7 Headset | FSA Orbit C-40 (No. 42) Sealed 1 ¹ / ₈ ACB Top . 1.5" Industrial Sealed Btm |
| 8 Hubs | 20H/24H x 14G Sealed Bearing Low- Flange Flip - Flop Hub (16T Cog) |
| 9 Saddle | Black Microfiber & Polyurethane foam |
| 10 Seatpost | State Oversized 31.6mm |
| 11 Stem | State 3D-Forged EXT 90mm |
| 12 Tires | Maxxis Pursuer 700 x 25c (Presta Long Valve Tube) |
| 13 Wheels | Bolt 31mm Alloy Track Wheelset 2130g (set) w/ Starfish Hub |

Total Weight: 16lbs 6 oz

BICYCLE SIZING AND GEOMETRY

| INSEAM (IN.) | HEIGHT (IN.) | FRAME SIZE (CM) | A CHAIN STAY (CM) | B EFFECTIVE TOP TUBE (CM) | C FORK OFFSET (CM) | D HEAD TUBE (CM) | E HEAD TUBE ANGLE | F SEAT TUBE (CM) | G SEAT TUBE ANGLE |
|-----------------|-----------------|--------------------|-------------------------|---------------------------------|--------------------------|------------------------|-------------------------|------------------------|-------------------------|
| 26.5"-28" | 5'0"-5'4" | 49 | 38.8 | 52.5 | 4.5 | 11.5 | 74.5° | 49 | 74.5° |
| 28"-30" | 5'4"-5'7" | 52 | 38.8 | 54 | 4.5 | 11.5 | 74.5° | 52 | 74.5° |
| 29.5-31" | 5'7"-5'11" | 55 | 38.8 | 55.5 | 4.5 | 13 | 74.5° | 55 | 73.5° |
| 31"-34" | 5'11"-6'2" | 58 | 38.8 | 57 | 4.5 | 16 | 74.5° | 58 | 73.5° |
| 34"-36" | 6'2"-6'5" | 61 | 38.8 | 59 | 4.5 | 20 | 74.5° | 62 | 73.5° |

DETAILED SIZING AND SPEC GUIDE

| | 49cm | 52cm | 55cm | 58cm | 61cm |
|----------------------------------|-------------|-------------|-------------|-------------|-------------|
| ACTUAL TOP TUBE LENGTH | 525mm | 544mm | 557mm | 572mm | 588mm |
| BB DROP | 45mm | 45mm | 45mm` | 45mm | 45mm |
| BB HEIGHT | 268.5mm | 268.5mm | 268.5mm | 268.5mm | 268.5mm |
| CHAIN STAY LENGTH | 388mm | 388mm | 388mm | 388mm | 388mm |
| COMPLETE BIKE WEIGHT | 7343g | 7399g | 7428g | 7455g | 7541g |
| CRANK ARM LENGTH | 170mm | 170mm | 170mm | 170mm | 170mm |
| EFFECTIVE TOP TUBE LENGTH | 525mm | 540mm | 555mm | 570mm | 590mm |
| FORK LENGTH | 370mm | 370mm | 370mm | 370mm | 370mm |
| FORK OFFSET | 45mm | 45mm | 45mm | 45mm | 45mm |
| FRAME SET WEIGHT | 1899g | 1956g | 1985g | 2050g | 2126g |
| HEAD TUBE ANGLE | 74.5° | 74.5° | 74.5° | 74.5° | 74.5° |
| HEAD TUBE LENGTH | 115mm | 115mm | 130mm | 160mm | 200mm |
| REACH | 396mm | 407mm | 403mm | 409mm | 417mm |
| SEAT TUBE | 490mm | 520mm | 550mm | 58mm | 620mm |
| SEAT TUBE ANGLE | 74.5° | 74.5° | 73.5° | 73.5° | 73.5° |
| STACK | 498mm | 498mm | 513mm | 545mm | 586mm |
| STANDOVER HEIGHT | 752mm | 765mm | 786mm | 815mm | 857mm |
| WHEEL BASE | 972mm | 982mm | 983mm | 984mm | 999mm |

DETAILED SIZING AND SPEC GUIDE

BOTTOM BRACKET

BSA Bottom Bracket
English Threaded
68mm

BRAKES

Dual Pivot
Forged Alloy
Clamp Diameter: 24mm

CHAIN

KMC Z710

CHAINRING

Forged 6061 Aluminum
48T
144 BCD

CRANK

Forged 7075 Aluminum
Crank Arm Length: 170mm

FORK

Full Carbon Fork and Steerer
1½" to 1⅛" Tapered Steerer

FRAME

Double Butted Y9 Kinesis
Aluminum Alloy
1½" to 1⅛" Tapered Headtube

HANDLEBARS

Aluminum
Width: 420mm
Drop/Reach: 130mm / 75mm

HEADSET

FSA #42 ACB

HUBS

Sealed Bearing, Flip-Flop Hub
16T Freewheel and Fixed Cog
Spacing: F: 100mm / R: 120mm
Bolts: F: M9 / R: M10

PEDALS

Not Included

SADDLE

Polyurethane
Steel Rails

SEAT POST

Aluminum
Diameter: 31.6mm
Length: 350mm

SEAT POST CLAMP

Aluminum
Diameter: 34.9mm

SPOKES

14G, 1 Cross Pattern

STEM

Forged Aluminum
Clamp Diameter: 31.8mm
Length: 90mm
Rise: +/- 7°

TIRES

Maxxis Pursuer
700c x 25mm
Suggested Max Tire F/R: 25mm / 28mm

WHEELS

700c Aluminum Wheel Set
Mid Profile Rim Depth: 30mm