

24XX - FLOOR COVER TRANSPORT/STORAGE CART

FLOOR COVER TRANSPORT/ STORAGE SYSTEM

SPECIFICATIONS

PORTER No. 92418ZZ VINYL COATED FLOOR COVER FABRIC

ZZ – Designates Color: 01 = Light Blue, 02 = Royal Blue, 03 = Red, 04 = White, 05 = Orange, 06 = Yellow Gold, 08 = Tan, 09 = Gray, 10 = Maroon, 11 = Purple, 12 = Black, 13 = Navy Blue, 14 = Kelly Green, 15 = Dark Green

Vinyl-coated floor cover fabric shall be of a heavy-duty (19 oz. per sq. yd.), polyester-reinforced fabric with superior wearability. Vinyl shall have a flame resistance to meet NFPA 701, UL-214 and the California State Fire Marshal requirements.

Cover material shall include a 10' wide Velcro pile strip sewn to one end of the vinyl. Matching strips of peel & stick Velcro hook shall be provided, to be applied to the batten tube assembly on the storage cart, allowing the cover section to be secured to the storage cart guickly and easily.

Cover sections shall be furnished as standard in 10'-0" (3.05m) widths, in lengths not to exceed 120'-0" (36.5m) to facilitate handling.

PORTER No. 924XXZZ VINYL COATED FLOOR COVER FABRIC

XX - Designates Quantity of Cover Sections: Even Amounts 04 thru 12

Overall size of transport cart shall be 2'-6" (76.2cm) in width x 4'-6" (1.38m) in height x 12'-0" (3.66m) in length.

Cart shall be capable of storing from four to twelve rollers, each of which will store 10' wide by maximum 120' long cover sections.

Batten tube assemblies shall be of heavy-wall plated steel tubing with internal pin arrangement, to accept dual hand cranks to facilitate ease of rolling of cover material. Batten tube assemblies shall operate in roller bearing-type support assemblies. Support assembly at one end of each batten tube shall be furnished with a ratchet-type lock system to prevent material from inadvertently unrolling in transport or storage locations. Batten tube assemblies shall be furnished with Velcro for ease of securing cover sections.

Transport frame shall consist of two (2) unitized A-Frame type assemblies fabricated from square heavy-wall structural tubing. Lower frame spreader shall be furnished with heavy mounting plates for attaching four (4) heavy-duty, 6" diameter swivel casters with 2" tread-width non-marking polyurethane wheels. Two (2) casters shall be equipped with a foot-operated locking mechanism to hold cart in place while rolling cover sections onto batten tube assemblies. End frame supports shall be secured in position by means of heavy horizontal spreaders and diagonal, X-type bracing to provide maximum stability. Entire frame assembly is finished in a durable blue enamel.

APPROXIMATE WEIGHT OF COMPLETE SYSTEM WITH MAXIMUM LENGTH (120') COVER SECTIONS								
Cart	Qty. Of	Total	Cart	Qty. Of	Total	Cart	Qty. Of	Total
Number	Covers	Weight	<u>Number</u>	Covers	Weight	<u>Number</u>	Covers	Weight
2404	4	1110 lbs	2408	8	1970 lbs	2412	12	2830 lbs
2406	6	1540 lbs	2410	10	2400 l bs			

OPTIONAL ITEMS TO SPECIFY

- See Page No. G-2405 for specifications on Porter No. 02405-000 Electric Power Winder.
- See Page No. G-2406 for specifications on Porter No. 02406-200 Hand-Held Tape Applicator.
- See Page No. G-2406 for specifications on Porter No. 02406-300 Walk-Type Tape Applicator.
- See Page No. G-2406 for specifications on Porter No. 02406-112 Floor Cover Seam Tape (12 Rolls).
- Porter No. 92404-000 Storage Cart Dust Cover Specify color (Sky Blue, Royal Blue, Red, White, Orange, Yellow, Beige, Gray, Maroon, Purple, Black, Navy, Kelly Green, Dark Green).