



Installation and Use Instructions for GRIPPS® Dropped Tool Prevention Equipment.

GRIPPS® Tool Grapple®
Models: H01122-D, H01123-D



H01122-D
Tool Grapple®
Max Load: 2.5kg/5.0lbs
Max Length: 125cm/49"



H01123-D
Tool Grapple® With Auto-Stop
Max Load: 2.5kg/5.0lbs
Max Length: 125cm/49"

For product support contact us at:

support@gripps.com.au | +61 3 8383 9458

WWW.GRIPPS.COM.AU | @GRIPPSGLOBAL | #CONQUERGRAVITY

GRIPPS® Tool Grapple®

SAFETY INFORMATION

⚠️ WARNING Before using the GRIPPS® Tool Grapple®, read all provided safety information pertaining to the use of your Dropped Tool Prevention (DTP) device. **FAILURE TO DO SO COULD RESULT IN INJURY OR DEATH.**

The user of a DTP device bears the responsibility of reading all safety information contained herein. Keep this manual for future reference.

Intended Use:

When used properly, the GRIPPS® Tool Grapple® can prevent workplace hazards resulting from dropped tools. These may include personal injury and material damage.

GRIPPS® does not approve use of this device for any activities not described in the User Instructions. This device is not intended to be used in any recreational activity, as a personal fall-arrest device or in any other manner not described herein.

⚠️ WARNING Misuse of this device could result in serious injury or death.

Adhere to all manufacturer recommendations regarding the operation and maintenance of this device. For additional information, contact GRIPPS® customer support.

Read and adhere to the following in order to ensure correct operational functionality:

- Your DTP should never be used as a personal fall-arrest device or restraint system.
- Do not use this device with tools that exceed the specified maximum load/weight.
- A DTP device used in applications that exceed the limits of operation specified by the manufacturer should be considered unsafe and should be replaced.
- Do not tether a tool over 2.5kg/5.5lbs directly to your clothing or person.
- Inspect your DTP device before each use.
- Ensure the DTP device is securely connected to a load rated tool connector or anchor point before use.
- Inspect any tool connector point before it is connected to the DTP device.
- Modification of the DTP device voids all warranties and violates manufacturer recommendations.
- Do not use a tool that cannot be connected to your DTP in the manner specified by GRIPPS®.
- It is unsafe to extend the length of the DTP product by any means.
- Do not use this product if it will create an unsafe working environment.
- Use extra precaution around moving machinery, moving parts, electrical hazards, extreme temperatures, chemical hazards, or combustion hazards.
- Avoid contact between the Tool Grapple® cable and rough or sharp edges.
- All connected tools and equipment, including connection points, must be compatible for use with this DTP device.
- Always wear appropriate personal protective equipment.

- If a tether has arrested a dropped tool or object, it should be taken out of service and replaced.
- All procedures shown in this instruction are for GRIPPS® Tool Grapple products only.

GENERAL USE AND CARE

The GRIPPS® Tool Grapple® is designed to provide a compact tethering solution for most handheld tools. The load rated synthetic housing allows the Tool Grapple® to be mounted to a belt or harness.

Recommended Use of GRIPPS® Tool Grapples:

1. Use for tools under 2.5kg/5.0lbs
2. When anchoring to Belts or Harnesses, inspect the material to ensure there is no visible damage or fraying.
3. When anchoring to the wrist, only use in conjunction with GRIPPS® Wrist Anchors.

Before Use:

Thoroughly inspect your GRIPPS® DTP device before each use. Do not use any component that presents deformities or deterioration.

Tool Grapple Usage Instructions:

To anchor Tool Grapple® to a harness or belt

1. Slide belt through belt housing. If that is not possible, then unscrew belt cover from the Tool Grapple® housing.



2. Place harness or belt on Tool Grapple® then screw belt cover on.



3. Ensure position of the Tool Grapple® does not interfere with the functionality of the harness.



To connect Tool Grapple® to a tool

1. Twist the carabiner lock in a counter-clockwise direction to unlock. Push the carabiner latch in and away from the carabiner opening. Connect the carabiner to the connector on the tool.



After Use Care:

Clean and inspect the Tool Grapple® and connected tool. For tougher stains, use warm water and a mild soap or detergent. Do not use again until dry.

Store in a clean and dry environment. Proper care will help to ensure that it will operate effectively and extend its service.



instagram.com/grippsglobal
facebook.com/grippsglobal
twitter.com/grippsglobal

Contact Support On
support@gripps.com.au
+61 3 8383 9458
#ConquerGravity