



Suite #133, 25 Storey Avenue Newburyport, MA 01950  
Phone: 978-465-2705 Email: rfoster@cenostar.

## Blanc Fixe N

### Typical Properties of CenoBar Blanc Fixe N

**Characteristics-** CenoBar-Blanc Fixe N is a functional extender for paints and coating, maximizing gloss and brilliance. Totally inert in ordinary conditions, and has high resistance to outdoor exposure and chemicals. Blanc Fixe is exceptionally bright because of its extreme purity. Its crystals are not acquired from a grinding process, but instead from solutions, allowing for low grit content. Blanc Fixe displays an incredibly fine and narrow particle size distribution. Due to low specific surface area, it has worthy wettability. Low Particle-size range for high gloss specifications.

**Applications-** CenoBar-Blanc Fixe uses include industrial paints, pigment pastes, high solids, base coats, primers, rubber industry, plastics, automotive coatings, powder coating systems, OEM and repair paint systems

#### Packaging:

CenoStar CenoBar-Blanc Fixe is supplied in 5kg, 50kg, 1000kg in plastic woven bag

#### Storage

Stored in unbroken packaging in dry, cool warehouse, CenoBar products will have a shelf-life of at least 24 months

#### Safety Information:

In dusty areas, the use of a NIOSH approved respirator is recommended. Material Safety Data Sheets (MSDS) are available upon request

Chemical Analysis (Typical)	
BaS04	99.00%
Volatile (105°C)%	<0.2
pH Value	9 ± 2
Electrical Conductivity	<250
Colorimetric Index (powder)	99%
Median Particle Size d50 (µm)	3 (± 0.5)
Screening >45 (µm)	≤0.01

#### Benefits of Blanc Fixe

- Cost Reduction of raw material
- Reduction of VOC
- Low abrasion during processing
- Reduction of solvent recovery
- Reduction of flocculation
- Improving weather resistance
- Resistant to acids and alkalis

**Notice to Purchaser:** The information in this publication is based on tests that we believe are reliable. Your results may vary due to differences in test conditions. You must evaluate and determine whether the product is suitable for your intended application. Since conditions of product use are outside of our control and may vary widely, the information is made available with no expressed or implied warranties (including the warranties of merchantability or fitness for a particular purpose). CenoStar Corporation's only obligation, and your only remedy, is replacement of product if shown to be defective when received. In no case will CenoStar Corporation be liable for any special, incidental, or consequential damages based on breach of warranty or contract, negligence, strict tort, or any other theory.