


# RWS 180 universal



## PRODUCT FEATURES

Peel & Stick easy to Install Heavy Duty Solar Charger | Jump Start Avoidance Battery Management | Maintenance Free | Fully Integrated DYNAMIC Solution with Patented Design, Optimized for Maximum Performance in scattered light & extreme weather conditions with Integrated charge controller.



## DYNAMIC RWS180 JUMP START AVOIDANCE TECHNICAL FEATURES

- RWS180-DCR
- Peel & Stick Simple Installation – DIY Friendly
- DYNAMIC Optimized Charge Controller for low-light and extreme weather conditions included for all makes and models.
- Hardware Wiring Kit included for all makes and models




## TECHNICAL SPECS


Cell Type	G1 Perc
Number in Series	36
Rated Pmax	180 Watts
Voltage Pmax	19.80 Vdc
Current Imp	9.00 Amp
Voc	23.90 Vdc
Isc	9.67 Amp
Active Area Efficiency	19%
Weight	9.15lb   4.15 kg
Thickness <sup>2</sup>	3mm
Battery Voltage	12V/24V
Charging Algorithm	3-Stage
Datalogging	Optional

## RWS180-DCR

Weight 9.15 lb | 4.15 kg



## SCHEMATIC CIRCUIT



1. Specifications are subject to change  
2. At the junction box area panel is 21mm high

UL Standard 1703  
Testing: Passed

IEC 61215/61730  
Testing: Passed



FOR MORE INFORMATION, CONTACT:

Colin Toews | 204 890-3011 | colin@dynamicssolar.ca