

# HIQ 077

# 15/6 Stainless body circulating pump

Power supply 230V/50Hz IP44  
Max head 6m  
Max Pressure 10 Bar  
Minimum pressure 0.3 Bar



Temperature rating 5 to 110 Deg C  
Max ambient temperature 35 Deg C

Pipe connections 1 " BSP Male  
Pump body (stainless) 130 mm  
Weight 2.58 Kgs

Suitable for closed and open vented applications  
Suitable for pottable water applications

Wiring connections should be made using  
0.75mm heat resistant flex in accordance with NZ  
Code.

All electrical work must be carried out by a suitably  
qualified electrician.



Speed 1	46W	3m head
Speed 2	67W	5m head
Speed 3	93W	6m head

Before installation the system if existing should be thoroughly flushed to remove all traces of sediment and solids.

It is recommended that the pump is fitted so that it can be isolated for service

**It is essential to ensure the pump is fitted with the body and shaft of the pump horizontal Under no circumstances should the body be vertical as this will damage the pump bearings causing premature failure.**

\*Do not install Motorized valves or restrictive flow components directly over the outlet or inlet

Ensure the install location allows sufficient access for wiring and use of the speed control.

No part of this pump should be within 25mm of a combustible surface



NZ C-tick E2564

[www.heatiq.co.nz](http://www.heatiq.co.nz)

**2YEAR  
WARRANTY**

This pump is manufactured to EN292, EN60335-1 and EN60335-2-51

Tradeport Ltd Heat IQ PO Box 530 Whanganui New Zealand [sales@heatiq.co.nz](mailto:sales@heatiq.co.nz)