

Utility HE Combi



The Utility Combi Boilers (UCHE) are compact yet extremely powerful.

At only 595mm wide they are similar in size to most standard kitchen appliances but are still capable of producing over 18 litres of hot water per minute. By utilising the latest twin pump technology and an integral thermal heat store within the boiler casing, the boilers are able to provide plenty of hot water when you need it, as well as helping to keep your heating costs to a minimum.

Key Features

- Available in outputs from 15 to 26kW
- Designed to fit neatly under standard work surfaces
- Stylish, pre-coated white casing
- Front servicing
- Complete with circulating pump, filling loop, pressure gauge and 12 litre expansion vessel
- Integral thermostatic mixing valve
- Suitable for use with conventional flues or with the multi-optional HE 'Easy-Fit' Balanced Flue System
- Riello RDB2.2 burner fitted as standard
- Optional 7-day digital programmer, for installation within the integrated the control panel

The Utility Combi Boilers (UCHE) are supplied fully pre-wired with a factory-fitted burner and control panel. Only one 3-pin mains socket (supplied) needs to be wired on site. The multi-optional flue system can be routed through the top, back, left or right hand side of the casing.

	UC70HE	UC90HE	UC120HE
Output (kW)	15-21	21-26	26-33
Flue Options	Conventional flue, low-level, high-level and vertical balanced flue		
Conventional flue size (mm)	100		
Sedbuk rating	A		
Height (mm)	865		
Depth (mm)	600		
Width (mm)	595		
Service access	Front/Top		
Condensate trap	Factory fitted		
Hot water flow rate (L/min)	18	24	24