



Residential / Light-commercial

Maximum comfort and versatility

The new Tivano fan coil range from Beretta are ideal for heating and cooling. Tivano can be placed almost anywhere thanks to its elegant design and very compact dimensions (just 150mm depth!)

Tivano can be used in conjunction with all Hydronic appliances inc, High temperature boiler systems and low temperature deliveries from heat pumps.

Tivano provides heating (or cooling) quickly and maintains the set level with pin point accuracy.

Available in 5 sizes, plus a high wall option Tivano offers a wide range of application possibilities.



Available with the touch screen interface control or with a remote controls interface.

Tivano is super efficient and easy to use.

Tivano DC-Inverter Technology

Tivano fan coil radiators use the latest permanent magnet motor technology to give superb performance. Tivano fan coils are significantly more effective than standard radiators, allowing high KW outputs from limited wall space.

They are also more than 30% more energy efficient than standard radiators.

Model	Unit	23	45	64	76	94	
Heating capacity 50 Deg input	W	1387	2720	3827	4572	5591	
Water flow rate required @ 50 Deg	L/h	185	357	558	653	769	
Heating capacity 70 Deg input	W	2374	4530	6436	7619	9356	
Water flow rate required@ 70Deg	L/h	202	390	553	655	805	
Sensitive Cooling capacity	W	829	1562	2517	2997	3565	
Pipe size F & R	mm	16	16	16	20	20	
H=579 + feet 80mm depth 150—L=	mm	723	923	1123	1323	1523	
Max power consumption	W	15.1	23.2	26.4	36	40.3	
Heat IQ purchase code		HIQ 603	HIQ 604	HIQ 605	HIQ 606	HIQ 607	

Testing to EN 1397 Compliance by RoHS Directive 2011/65 UE

Options/accessories	Feet kit-Hides F&R	Inlet valve kit	Inbuilt touch control	Remote stat interface	Soleniod valve kit (option)
	HIQ 608FT	HIQ 608T	HIQ 608IN	HIQ 608RE	HIQ 608SK

High wall model option **H64**

