



LED Selectable Commercial Recessed Downlights Diffuser Version

Specifications

Selectable Commercial Recessed Downlight Diffuser Version (27K,50K)

| ITEM # | DESCRIPTION | VOLTAGE | INCAND. WATTS | WATTAGE | LUMENS | | | | | | IPW | CRI | |
|---|-------------------------------------|---------|---------------|----------|--------|------|------|------|------|------|--|-----|--|
| | | | | | 27K | 50K | 27K | 50K | 27K | 50K | | | |
| 4" Selectable Commercial Recessed Downlight Diffuser Version – 65 Watt Replacement • 50,000 Hour | | | | | | | | | | | | | |
| DIC4SWUZDCC2 (Matte Silver Finish) | LED 4" Comm Downlight Diffuser CCT | 120/277 | 65 | 7/9/12 | 700 | 750 | 900 | 1000 | 1200 | 1300 | IW:100/107.1 MW:100/111.1 HW:100/108.3 | 80 | |
| DIC4SMUZDCC2W (White Finish) | | | | | | | | | | | | | |
| 6" Selectable Commercial Recessed Downlight Diffuser Version – 85 Watt Replacement • 50,000 Hour | | | | | | | | | | | | | |
| DIC6SWUZDCC2 (Matte Silver Finish) | LED 6" Comm Downlight Diffuser CCT | 120/277 | 85 | 8/10/15 | 700 | 750 | 1000 | 1050 | 1450 | 1500 | IW: 87.5/93.8 MW: 100/105 HW: 96.7/100 | 80 | |
| DIC6SMUZDCC2W (White Finish) | | | | | | | | | | | | | |
| 8" Selectable Commercial Recessed Downlight Diffuser Version – 85 Watt Replacement • 50,000 Hour | | | | | | | | | | | | | |
| DIC8SWUZDCC2 (Matte Silver Finish) | LED 8" Comm Downlight Diffuser CCT | 120/277 | 85 | 11/15/19 | 1200 | 1300 | 1600 | 1650 | 2000 | 2050 | IW:109.1/118.2 MW:106.7/110 HW:105.3/107.9 | 80 | |
| DIC8SMUZDCC2W (White Finish) | | | | | | | | | | | | | |
| 10" Selectable Commercial Recessed Downlight Diffuser Version – 100 Watt Replacement • 50,000 Hour | | | | | | | | | | | | | |
| DIC10SWUZDCC2 (Matte Silver Finish) | LED 10" Comm Downlight Diffuser CCT | 120/277 | 100 | 18/23/30 | 1800 | 1850 | 2250 | 2300 | 2850 | 2950 | IW:100/102.8 MW: 97.8/100 HW: 95.9/98.3 | 80 | |
| DIC10SMUZDCC2W (White Finish) | | | | | | | | | | | | | |
| 12" Selectable Commercial Recessed Downlight Diffuser Version – 125 Watt Replacement • 50,000 Hour | | | | | | | | | | | | | |
| DIC12SWUZDCC2 (Matte Silver Finish) | LED 12" Comm Downlight Diffuser CCT | 120/277 | 125 | 18/23/30 | 1800 | 1850 | 2250 | 2300 | 2850 | 2950 | IW:100/102.8 MW: 97.8/100 HW: 95.9/98.3 | 80 | |
| DIC12SMUZDCC2W (White Finish) | | | | | | | | | | | | | |

Optional Accessories

| ITEM NUMBER | DESCRIPTION | DIMENSIONS |
|----------------|--|-----------------------|
| EMBACKUPCOMDL1 | EMERGENCY BACKUP FOR 4" AND 6" SELECTABLE COMMERCIAL DOWNLIGHT | 9.45" X 1.77" X 1.18" |
| EMBACKUPCOMDL2 | EMERGENCY BACKUP FOR 8", 10" AND 12" SELECTABLE COMMERCIAL DOWNLIGHT | 12.9" X 2.6" X 2.2" |



RoHS
Compliant

5 Year
WARRANTY

*Based on 12 hours use per day