



10W Natural White LED ECO Globe Edison Screw

VBELG-ES-10W5K



VIBE's Eco Range GLS Lamps are designed in an attractive, convenient barcoded hangsell twin pack for display or just an economical way to purchase your lamps. Available in a Warm White or Cool White colour and in various bases to suit your application.

Features & Benefits

- Direct replacement for incandescent GLS lamps
- Equipped with high quality EPISTAR LED chips
- Supplied as a Twin Pack
- Available in ES & BC lamp base
- 25,000 hr lifespan
- 2 year warranty

10W Natural White LED ECO Globe Edison Screw

VBELG-ES-10W5K

Specifications

SKU	VBELG-ES-10W5K
Luminaire efficacy	110
EAN	9340994405384
Light Colour	Natural White
Wattage	10
Lumen output	1100
CRI	80
Beam Angle	270
Base Type	E27
Length	110
Width	60
Lifespan	25000
Warranty	2
LED source	Epistar
Material	PC diffuser with plastic coated aluminum body
Lamp Type	LED
Input voltage	220V-265V AC 50hz
Working temperature	-20°C ~ 45°C
Kelvin	5000K



Photometric information available upon request.



10W Warm White LED ECO Globe Bayonet Cap

VBELG-BC-10W3K



VIBE's Eco Range GLS Lamps are designed in an attractive, convenient barcoded hangsell twin pack for display or just an economical way to purchase your lamps. Available in a Warm White or Cool White colour and in various bases to suit your application.

Features & Benefits

- Direct replacement for incandescent GLS lamps
- Equipped with high quality EPISTAR LED chips
- Supplied as a Twin Pack
- Available in ES & BC lamp base
- 25,000 hr lifespan
- 2 year warranty

10W Warm White LED ECO Globe Bayonet Cap

VBELG-BC-10W3K

Specifications

SKU	VBELG-BC-10W3K
Luminaire efficacy	105
EAN	9340994405353
Light Colour	Warm White
Wattage	10
Lumen output	1050
CRI	80
Beam Angle	270
Base Type	B22
Length	110
Width	60
Lifespan	25000
Warranty	2
LED source	Epistar
Material	PC diffuser with plastic coated aluminum body
Lamp Type	LED
Input voltage	220V-265V AC 50hz
Working temperature	-20°C ~ 45°C
Box Qty	60
Kelvin	3000K



Photometric information available upon request.



10W Natural White LED ECO Globe Bayonet Cap

VBELG-BC-10W5K



VIBE's Eco Range GLS Lamps are designed in an attractive, convenient barcoded hangsell twin pack for display or just an economical way to purchase your lamps. Available in a Warm White or Cool White colour and in various bases to suit your application.

Features & Benefits

- Direct replacement for incandescent GLS lamps
- Equipped with high quality EPISTAR LED chips
- Supplied as a Twin Pack
- Available in ES & BC lamp base
- 25,000 hr lifespan
- 2 year warranty

10W Natural White LED ECO Globe Bayonet Cap

VBELG-BC-10W5K

Specifications

SKU	VBELG-BC-10W5K
Luminaire efficacy	110
EAN	9340994405360
Light Colour	Natural White
Wattage	10
Lumen output	1100
CRI	80
Beam Angle	270
Base Type	B22
Length	110
Width	60
Lifespan	25000
Warranty	2
LED source	Epistar
Material	PC diffuser with plastic coated aluminum body
Lamp Type	LED
Input voltage	220V-265V AC 50hz
Working temperature	-20°C ~ 45°C
Box Qty	60
Kelvin	5000K



Photometric information available upon request.



10W Warm White LED ECO Globe Edison Screw

VBELG-ES-10W3K



VIBE's Eco Range GLS Lamps are designed in an attractive, convenient barcoded hangsell twin pack for display or just an economical way to purchase your lamps. Available in a Warm White or Cool White colour and in various bases to suit your application.

Features & Benefits

- Direct replacement for incandescent GLS lamps
- Equipped with high quality EPISTAR LED chips
- Supplied as a Twin Pack
- Available in ES & BC lamp base
- 25,000 hr lifespan
- 2 year warranty

10W Warm White LED ECO Globe Edison Screw

VBELG-ES-10W3K

Specifications

SKU	VBELG-ES-10W3K
Luminaire efficacy	105
EAN	9340994405377
Light Colour	Warm White
Wattage	10
Lumen output	1050
CRI	80
Beam Angle	270
Base Type	E27
Length	110
Width	60
Lifespan	25000
Warranty	2
LED source	Epistar
Material	PC diffuser with plastic coated aluminum body
Lamp Type	LED
Input voltage	220V-265V AC 50hz
Working temperature	-20°C ~ 45°C
Kelvin	3000K



Photometric information available upon request.