



Vibe 10W LED R80 ES 5000K Non Dimmable

VBLR80-10W-5K



VIBE Lighting R80 Natural White LED Lamps are traditionally a direct replacement for 100W reflector globes in 3-in-1 bathroom fittings. They are rated at 25,000hrs and feature a 2 year warranty for decreased maintenance.

Features & Benefits

- Direct replacement of 100W R80 Reflector lamps
- Unique anti-glare optical design with frosted diffuser
- Equipped with energy efficient EPISTAR LED chips, high luminaire efficacy
- Polycarbonate face and body
- Environmentally friendly
- 25,000 hour lifespan
- 2 year warranty




Specifications

SKU	VBLR80-10W-5K
Luminaire efficacy	85
EAN	9340994018751
Light Colour	Natural White
Wattage	10
Lumen output	850
CRI	80
Beam Angle	120
Base Type	E27
Diameter	80
Length	113
Lifespan	25000
Warranty	2
Dimmable	Non-Dimmable
LED source	Epistar
Material	Thermal Plastic
Lamp Type	LED
Input voltage	220V-240V AC 50HZ
Weatherproof	Indoor Use Only
Working temperature	-20°C ~ 50°C
Box Qty	50
Kelvin	5000K



Dimensional Drawings



 ${\it Photometric\ information\ available\ upon\ request.}$







Vibe 10W LED R80 ES 3000K Non Dimmable

VBLR80-10W-3K



VIBE Lighting R80 Warm White LED Lamps are traditionally a direct replacement for 100W reflector globes in 3-in-1 bathroom fittings. They are rated at 25,000hrs and feature a 2 year warranty for decreased maintenance.

Features & Benefits

- Direct replacement of 100W R80 Reflector lamps
- Unique anti-glare optical design with frosted diffuser
- Equipped with energy efficient EPISTAR LED chips, high luminaire efficacy
- Polycarbonate face and body
- Environmentally friendly
- 25,000 hour lifespan
- 2 year warranty




Specifications

	VDI DOO 10W 2V
SKU	VBLR80-10W-3K
Luminaire efficacy	80
EAN	9340994018744
Light Colour	Warm White
Wattage	10
Lumen output	800
CRI	80
Beam Angle	120
Base Type	E27
Diameter	80
Length	113
Lifespan	25000
Warranty	2
Dimmable	Non-Dimmable
LED source	Epistar
Material	Thermal Plastic
Lamp Type	LED
Input voltage	220V-240V AC 50HZ
Weatherproof	Indoor Use Only
Working temperature	-20°C ~ 50°C
Box Qty	50
Kelvin	3000K



Dimensional Drawings



Photometric information available upon request.

