



## 545 Series

### VBLFT-545-F-65



Vibe 20W Daylight Aluminium Body LED Tube

#### Features & Benefits

- Specially designed Aluminium body with excellent heat dissipation
- Direct replacement for 4FT T8 fluorescent tubes
- Compatible with most RAPID START MAGNETIC OR ELECTRONIC BALLASTS
- Frosted cover Equipped with high powered EPISTAR SMD LED chips
- Environmentally friendly
- 50,000 hour lifespan
- 3 year warranty




## Specifications

<b>SKU</b>	VBLFT-545-F-65
<b>Luminaire efficacy</b>	110
<b>EAN</b>	9340994405506
<b>Light Colour</b>	Daylight
<b>Wattage</b>	20
<b>Lumen output</b>	2200
<b>CRI</b>	80
<b>Beam Angle</b>	140
<b>Base Type</b>	G13
<b>Diameter</b>	26
<b>Length</b>	1198
<b>Lifespan</b>	50000
<b>Warranty</b>	3
<b>LED source</b>	Epistar
<b>Lamp Type</b>	LED
<b>Input voltage</b>	85V-265V AC 50-60HZ
<b>Diffuser</b>	Frosted
<b>Working temperature</b>	-20°C ~ 40°C
<b>Box Qty</b>	40



## Dimensional Drawings



*Photometric information available upon request.*



## Vibe 20W Cool White Aluminum Body LED Tube

**VBLFT-545-F-40**



Featuring a specially designed aluminium body, frosted cover and an energy saving of up to 60% the LED Tube Lamps make great direct replacements for 4 foot T8 fluorescent lamps.

### Features & Benefits

- Specially designed Aluminium body with excellent heat dissipation
- Direct replacement for 4FT T8 fluorescent tubes
- Compatible with most RAPID START OR ELECTRONIC BALLASTS
- Frosted cover Equipped with high powered EPISTAR SMD LED chips
- Environmentally friendly
- 50,000 hour lifespan
- 3 year warranty



# Vibe 20W Cool White Aluminum Body LED Tube

**VBLFT-545-F-40**

## Specifications

<b>SKU</b>	VBLFT-545-F-40
<b>Luminaire efficacy</b>	105
<b>EAN</b>	9340994402413
<b>Light Colour</b>	Cool White
<b>Wattage</b>	20
<b>Lumen output</b>	2100
<b>CRI</b>	80
<b>Beam Angle</b>	140
<b>Base Type</b>	G13
<b>Diameter</b>	26
<b>Length</b>	1198
<b>Lifespan</b>	50000
<b>Warranty</b>	3
<b>LED source</b>	Epistar
<b>Lamp Type</b>	LED
<b>Input voltage</b>	85V-265V AC 50-60HZ
<b>Diffuser</b>	Frosted
<b>Working temperature</b>	-20°C ~ 40°C
<b>Box Qty</b>	30



*Photometric information available upon request.*