

# 24V CONSTANT VOLTAGE IP67

EV-DRIVER-24V-40W-ND

Constant Voltage Led Driver IP67 to suit 24V led arrays



## ORDERING INFORMATION

Order code	16089
Description	40W 24V Constant Voltage Driver IP67 with 1m Flex and plug
Driver Power	40 W
Driver Type	Fixed output
Item Code	EV-DRIVER-24V-40W-ND

## MECHANICAL

Body Material	Aluminium
Product Finish	Anodised
IC Rating	Non-IC
IP Rating	IP67

## ELECTRICAL

Electrical Rating	Class I
Input Current	0.5 A
Input Frequency	50/60 Hz
Input voltage	100-240Vac
Power Factor	0.95
Switch Type	Inline
Working Temp Range	-20 to 50 °C

## DRIVER

Dimmable	No
Driver Mode	Constant Voltage
Driver Type	Fixed output
Flex & Plug or Lead Length	1000 mm
Wiring Type	Re-wireable Flex & Plug (3 pin)
Driver Power	40 W
Driver Current	1670 mA
Output Voltage Range	24 V

## COMPLIANCE

Standards	AS/NZS 61347.1 AS/NZS 61347.2.13 IEC 62493 AS/NZS 3100 EN 55015 EN 61000.3.2 EN 61000.3.3 EN 61547
-----------	---

## DIMENSIONS

Product Height	31 mm
Product Length	182 mm
Product Width	58 mm



# 24V CONSTANT VOLTAGE IP67

EV-DRIVER-24V-200W-ND

Constant Voltage Led Driver IP67 to suit 24V led arrays



## ORDERING INFORMATION

Order code	16093
Description	200W 24V Constant Voltage Driver IP67 with 1m Flex and plug
Driver Power	200 W
Driver Type	Fixed output
Item Code	EV-DRIVER-24V-200W-ND

## MECHANICAL

Body Material	Aluminium
Product Finish	Anodised
IC Rating	Non-IC
IP Rating	IP67

## ELECTRICAL

Electrical Rating	Class I
Input Current	2.1 A
Input Frequency	50/60 Hz
Input voltage	100-240Vac
Power Factor	0.95
Switch Type	Inline
Working Temp Range	-20 to 50 °C

## DRIVER

Dimmable	No
Driver Mode	Constant Voltage
Driver Type	Fixed output
Flex & Plug or Lead Length	1000 mm
Wiring Type	Re-wireable Flex & Plug (3 pin)
Driver Power	200 W
Driver Current	8340 mA
Output Voltage Range	24 V

## COMPLIANCE

Standards	AS/NZS 61347.1 AS/NZS 61347.2.13 IEC 62493 AS/NZS 3100 EN 55015 EN 61000.3.2 EN 61000.3.3 EN 61547
-----------	---

## DIMENSIONS

Product Height	42 mm
Product Length	250 mm
Product Width	72 mm

# 24V CONSTANT VOLTAGE IP67

EV-DRIVER-24V-150W-ND

Constant Voltage Led Driver IP67 to suit 24V led arrays



## ORDERING INFORMATION

Order code	16092
Description	150W 24V Constant Voltage Driver IP67 with 1m Flex and plug
Driver Power	150 W
Driver Type	Fixed output
Item Code	EV-DRIVER-24V-150W-ND

## MECHANICAL

Body Material	Aluminium
Product Finish	Anodised
IC Rating	Non-IC
IP Rating	IP67

## ELECTRICAL

Electrical Rating	Class I
Input Current	1.8 A
Input Frequency	50/60 Hz
Input voltage	100-240Vac
Power Factor	0.95
Switch Type	Inline
Working Temp Range	-20 to 50 °C

## DRIVER

Dimmable	No
Driver Mode	Constant Voltage
Driver Type	Fixed output
Flex & Plug or Lead Length	1000 mm
Driver Power	150 W
Driver Current	6250 mA
Output Voltage Range	24 V

## COMPLIANCE

Standards	AS/NZS 61347.1 AS/NZS 61347.2.13 IEC 62493 AS/NZS 3100 EN 55015 EN 61000.3.2 EN 61000.3.3 EN 61547
-----------	---

## DIMENSIONS

Product Height	40 mm
Product Length	220 mm
Product Width	70 mm

# 24V CONSTANT VOLTAGE IP67

EV-DRIVER-24V-100W-ND

Constant Voltage Led Driver IP67 to suit 24V led arrays



## ORDERING INFORMATION

Order code	16091
Description	100W 24V Constant Voltage Driver IP67 with 1m Flex and plug
Driver Power	100 W
Driver Type	Fixed output
Item Code	EV-DRIVER-24V-100W-ND

## MECHANICAL

Body Material	Aluminium
Product Finish	Anodised
IC Rating	Non-IC
IP Rating	IP67

## ELECTRICAL

Electrical Rating	Class I
Input Current	1.5 A
Input Frequency	50/60 Hz
Input voltage	100-240Vac
Inrush Current	1.5 A
Power Factor	0.95
Switch Type	Inline
Working Temp Range	-20 to 50 °C

## DRIVER

Dimmable	No
Driver Mode	Constant Voltage
Driver Type	Fixed output
Flex & Plug or Lead Length	1000 mm
Wiring Type	Re-wireable Flex & Plug (3 pin)
Driver Power	100 W
Driver Current	4170 mA
Output Voltage Range	24 V

## COMPLIANCE

Standards	AS/NZS 61347.1 AS/NZS 61347.2.13 IEC 62493 AS/NZS 3100 EN 55015 EN 61000.3.2 EN 61000.3.3 EN 61547
-----------	---

## DIMENSIONS

Product Height	35 mm
Product Length	199 mm
Product Width	67 mm